

LOS ANGELES COUNTY SHERIFF'S DEPARTMENT



40th Annual

LAW ENFORCEMENT VEHICLE TEST AND EVALUATION PROGRAM

VEHICLE MODEL YEAR 2015

Jim McDonnell, SHERIFF

TABLE OF CONTENTS

| | |
|---|-----|
| Introduction..... | 3 |
| Acknowledgements..... | 4 |
| Test Vehicle Description..... | 6 |
| Vehicle Specifications..... | 8 |
| 32 Lap High Speed Vehicle Evaluation..... | 23 |
| Pursuit Course Evaluation..... | 52 |
| Brake Evaluation..... | 67 |
| Acceleration Evaluation..... | 69 |
| Heat Evaluation..... | 72 |
| Communication Evaluation..... | 76 |
| Ergonomic Evaluation..... | 89 |
| Fuel Efficiency Evaluation..... | 114 |

PREFACE

The Los Angeles County Sheriff's Department first implemented its police vehicle testing program in 1974. Since that time, our department has become nationally recognized as a major source of information relative to police vehicles and their use. It is our goal to provide law enforcement agencies with the information they require to successfully evaluate those vehicles currently being offered for police service. The Los Angeles County Sheriff's Department is proud to publish this information, via the internet, to all law enforcement agencies.

Since the inception of our vehicle testing program in 1974, we have continually refined our efforts in this area in order to provide the law enforcement community with the most current information available. During the 1997 model year testing, the Sheriff's department expanded its existing criteria to include an urban or "city street" pursuit course. This course consists of multiple city block distances punctuated by the various types of turns normally found in most inner city environments. The "city street" course is designed to simulate the conditions encountered by most officers working in typical urban communities. The test is only conducted on vehicles offered with a factory "Police Package". Since many law enforcement agencies buy "non-pursuit" vehicles, we also test vehicles offered in a "Special Service" configuration when offered by the manufacturers. These vehicles are tested in a similar fashion as "Police Package" vehicles however we do not subject them to the city street pursuit course.

The booklet is not intended as a recommendation for any specific vehicle contained within. The Sheriff's Department conducts the vehicle testing program in order to accomplish two primary goals. To provide law enforcement agencies with the data necessary to assist those in the vehicle selection process, and to provide the various vehicle manufacturers with the input necessary to better meet the needs of law enforcement. We recognize the fact that individual agency needs can be influenced by cost, operational considerations and other factors.

Our testing process is designed to address the law enforcement officer's operational requirements in terms of vehicle performance, vehicle safety, and comfort.

Each test is designed and executed to simulate actual field conditions as closely as possible. The vehicles being tested are driven on city streets and interstates, as well as the performance track, by law enforcement personnel. The maneuvers duplicated during the electronic test procedures are those encountered in actual patrol and emergency operations which the law enforcement officer may encounter in the field.

Interpretation of test results is the responsibility of each agency. The importance with which each individual phase is weighted is a subjective decision which should be made by each agency based upon that agency's needs.

ACKNOWLEDGEMENTS

The Los Angeles County Sheriff's Department, Fleet Management Bureau would like to thank all those who have contributed their time and efforts in making this year's test a success.

Vehicle Test Track Drivers

Deputy Robert Robinson - LASD
Deputy Ramiro Juarez - LASD

Officer Carrie Dooros -LAPD
Officer Gary Correa -LAPD

Vehicle Manufactures

Ford Motor Company
Chevrolet

General Motors
Chrysler

Support Personnel

LASD Food Services
LASD Sign Shop
LASD Print Shop
LASD Video Production Unit
LASD Web Development Unit
Reserve Forces Bureau
ASAP Team
AERO Bureau
Max Thomson (Test Consultant)
Hiroshi Aramaki (Test Director)
Rochelle Kidd (Vendor Coordinator)
Guadalupe La Voie, LET

Yolanda Gomez, LET
Marcia Molinari, LET
Kalila Lujan, OAI
Lorena Sigala, OAI
Dep. Jeff Tesdahl (EOB)
Dep. Steve Woolum (SSB)
Juan Amaya (FSB)
Joe Rosales (EVOC)
Sgt. Michael Jones (TSB)
Bruce Wheeler (Penske)
Robert Yip (Penske)
Joe Shunping (Penske)

Vehicle Evaluation Team

Ergonomic Drivers

Dep. Andrew Gill
Dep. Andrew Leos
Dep. Michael Markman
Dep. Lina Pimental
Dep. Michael Reynolds
Dep. Sonia Tario
Dep. Marko Tinoco
Dep. Mike Quintero

Communication Noise

Richard Santivong, ECT Supervisor
Joe Nassar, ECT

Vehicle Test Sponsors

Federal Signal
Link Engineering
McPeck Dodge of Anaheim
RaceLogic, USA
Setina Manufacturing
West Coast Lights & Sirens
Westin Automotive

We would like to give a special thank you to the Auto Club Speedway Administrative Service Director, Brian Geve and his staff.

ACKNOWLEDGEMENTS

The Los Angeles County Sheriff's Department Fleet Management Bureau would like to thank the following companies for their participation and continued support of the LASD Vehicle Test vendor expo.

Adamson Police Products
Air-El
B&B Enterprises
BMW Motorrad, U.S.A.
Chrysler LLC. Law Enforcement
Crosssco / Code 3 Products
Cooks Communications Corp
Dura Tech U.S.A, Inc.
Factory Motor Parts
Federal Signal
Ford Motor Company Police Vehicles
General Motors Police Program
Harley Davidson Motor Company
Havis Inc.
Huntington Beach Motorsports
Jotto Desk
Lehr Auto Electric
Link Engineering Company
Mcpeeks Dodge of Anaheim
O' Reilly Auto Parts
911 Circuits

Piaggio Group Americas, Inc.
Pro-Gard Products, LLC.
Raceway Ford
Raybestos
Setina Mfg.
Sound Off Signal
Stalker Radar
Streaming Networks, Inc.
Stop Tech, Ltd.
Supersprings International
Tactical Command Cabinets
Tomar Electronics Inc.
Troy Products
Tuffy Security Products
Victory Police Motorcycles
Wattco Equipment Inc.
West Coast Lights & Siren Inc
Westin Public Safety Products
Zero Motorcycles
10-8 Retrofit Inc.

2015 MODEL YEAR VEHICLE TEST

On October 14th–17th, 2014, vehicle testing was performed at the AutoClub Speedway in Fontana, California. Chrysler, General Motors, and Ford all submitted vehicles in the “Police Package” category. Police Package vehicles have been identified by the manufacturers as pursuit vehicles. All of the vehicles submitted completed the test satisfactorily, without incident.

The vehicles submitted for evaluation were all 2015 models and are identified below.

HIGH SPEED POLICE PACKAGE VEHICLE CATEGORY:

- | | |
|------------------------------------|---|
| 2015 Ford PI Sedan FWD: | Full size four door sedan, front wheel drive, 3.5liter V-6 engine, 6 speed automatic transmission with overdrive and a 3.16 axle ratio. |
| 2015 Ford PI Sedan AWD: | Full size four door sedan, all-wheel drive, 3.7 liter V-6 engine, 6 speed automatic transmission with overdrive and a 3.39 axle ratio. |
| 2015 Ford PI EcoBoost Sedan AWD: | Full size four door sedan, all-wheel drive, 3.5 liter EcoBoost V-6 engine, 6 speed automatic transmission with overdrive and a 3.16 axle ratio. |
| 2015 Ford PI Utility AWD: | Full size four door sport utility, all-wheel drive, 3.7 liter V-6 engine, 6 speed automatic transmission with overdrive and a 3.65 axle ratio. |
| 2015 Ford PI EcoBoost Utility AWD: | Full size four door sport utility, all-wheel drive, 3.5 liter EcoBoost Twin Turbocharged V-6 engine, 6 speed automatic transmission with overdrive and a 3.16 axle ratio. |

HIGH SPEED POLICE PACKAGE VEHICLE CATEGORY: (CONTINUED)

| | | |
|------|---------------------------|---|
| 2015 | Chevrolet Impala Limited: | Full size four door sedan, front wheel drive, 3.6 liter V-6 engine, 6 speed automatic transmission with overdrive, and a 2.44:1 axle ratio. |
| 2015 | Chevrolet Tahoe PPV 2wd: | Full size four door sport utility, 2 wheel drive (rear), 5.3 liter V-8 engine, 6 speed automatic transmission with overdrive and a 3.08:1 axle ratio. |
| 2015 | Chevrolet Tahoe PPV 4wd: | Full size four door sport utility, 4 wheel drive, 5.3 liter V-8 engine, 6 speed automatic transmission with overdrive and a 3.08:1 axle ratio. |
| 2015 | Chevrolet Caprice V6: | Full size four door sedan, rear wheel drive, 3.6 liter V-6 engine, 6 speed automatic transmission with overdrive and a 2.92:1 axle ratio. |
| 2015 | Chevrolet Caprice V-8: | Full size four door sedan, rear wheel drive, 6.0 liter V-8 engine, 6 speed automatic transmission with overdrive and a 2.92:1 axle ratio. |
| 2015 | Dodge Charger V-6 2.62: | Full size four door sedan, rear wheel drive, 3.6 liter V-6 engine, 5 speed automatic transmission with overdrive and a 2.62:1 axle ratio. |
| 2015 | Dodge Charger V-6 3.07: | Full size four door sedan, rear wheel drive, 3.6 liter V-6 engine, 5 speed automatic transmission with overdrive and a 3.07:1 axle ratio. |
| 2015 | Dodge Charger V-8 RWD: | Full size four door sedan, rear wheel drive, 5.7 liter V-8 Hemi engine, 5 speed automatic transmission with overdrive and a 2.62:1 axle ratio. |
| 2015 | Dodge Charger V-8 AWD: | Full size four door sedan, all-wheel drive, 5.7 liter V-8 Hemi engine, 5 speed automatic transmissions with overdrive and a 3.06 axle ratio. |

VEHICLE SPECIFICATIONS

MAKE: 2015 Chevrolet**MODEL: Impala 9C1
SALES CODE # 1WS19**

| Vehicle Type front-engine, front wheel drive, 4-passenger, 4 door sedan, Police Package vehicle | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>17</td><td>28</td><td colspan="2">20 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 17 | 28 | 20 MPG* | | | |
|---|---|---|------|-----------|---------|---------|----------|---------|---------|----------|---------|---------|-----------|---------|---------|--|---|
| EPA | | TESTED | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | |
| 17 | 28 | 20 MPG* | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | <u>DIMENSIONS</u> | <u>CHASSIS</u> | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: High density foam bucket, 6 way power, manual lumbar Rear: Vinyl with high density foam bench MEASUREMENTS: <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>39.4 in</td><td>37.8 in</td></tr><tr><td>Legroom:</td><td>42.3 in</td><td>37.6 in</td></tr><tr><td>Shoulder</td><td>58.7 in</td><td>58.6 in</td></tr><tr><td>Hip Room:</td><td>56.4 in</td><td>57.2 in</td></tr></table> Interior Volume: Front: 56.6 cubic feet Rear: 48.2 cubic feet Comb: 105 cubic feet Trunk: 18.6 cubic feet | | Front | Rear | Headroom: | 39.4 in | 37.8 in | Legroom: | 42.3 in | 37.6 in | Shoulder | 58.7 in | 58.6 in | Hip Room: | 56.4 in | 57.2 in | Fuel Capacity: 66.2 Liters 17.5 Gallons GVW: 4,938 lbs. Wheelbase: 110.5 in Ground Clearance: 6.5 in Length: 200.4 in Height: 58.7 in | STEERING Power rack-and-pinion Curb-to-curb: 38 ft. SUSPENSION Front: Independent strut, coil springs and stabilizer bar Rear: Independent tri-link, coil spring over strut and stabilizer bar WHEEL+TIRES Wheel size/type: 17x7.5 steel, Tire type: Goodyear P235/55R17 W Rated BRAKES Power, dual hydraulic with antilock control Front: 12.7 inch vented disc Rear: 10.9 inch solid disc |
| | Front | Rear | | | | | | | | | | | | | | | |
| Headroom: | 39.4 in | 37.8 in | | | | | | | | | | | | | | | |
| Legroom: | 42.3 in | 37.6 in | | | | | | | | | | | | | | | |
| Shoulder | 58.7 in | 58.6 in | | | | | | | | | | | | | | | |
| Hip Room: | 56.4 in | 57.2 in | | | | | | | | | | | | | | | |
| <u>ENGINE</u> | <u>DRIVETRAIN</u> | | | | | | | | | | | | | | | | |
| Naturally aspirated V-6 Fuel delivery system: SIDI Cubic Inches: 217 Displacement: 3.6 Liters Compression Ratio: 11.5:1 Horse Power: 302 bhp @ 6800 rpm Torque (SAE net): 262 lb. feet @ 5300 rpm Alternator: 170 amp Battery: 720 CCA | Transmission: Model 6T70 6 speed automatic with overdrive and lockup torque converter and Axle Ratio: 2.44:1 | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 2.9 sec. 0-60mph – 7.2 sec 0-100mph – 18.4 sec 30-60mph – 4.3 sec 60-100mph – 11.4 sec ¼ mile –15.6 sec @ 91.9 mph | <u>BRAKING</u> 140.2 ft. @ 60 mph | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:28.1 Average Speed - 59.83 <u>PURSUIT</u> Average Lap Time - 4:37.52 Average Speed – 33.7 | | | | | | | | | | | | | | | |

MAKE: 2015 Chevrolet**MODEL: Tahoe 2WD (9C1)****SALES CODE # CC15706**

| | | | | | |
|--|-------------------------|--|-----|---------------------------|-----|
| Vehicle Type: front-engine, rear wheel drive, 4 door utility, Police Package vehicle | | EPA | | TESTED | |
| | | CITY | HWY | CITY | HWY |
| | | 16 | 23 | 12 MPG* | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | | |
| <u>SEATS:</u> | | <u>Fuel Capacity:</u> | | | |
| Front: Cloth bucket, 6 way power, manual lumbar and recline | | 98.0 Liters 26.0 Gallons | | | |
| Rear: Vinyl split-folding 60/40 Bench | | <u>GVWR:</u> 6,800 lbs. | | | |
| | | <u>Wheelbase:</u> 116 in | | | |
| <u>MEASUREMENTS:</u> | | <u>Ground Clearance:</u> 8.5 in | | | |
| | Front Rear | <u>Overall Length:</u> 204 in | | | |
| Headroom: | 42.8 in 38.7 in | <u>Overall Height:</u> 72.4 in | | | |
| Legroom: | 45.3 in 39.0 in | | | | |
| Shoulder | 64.8 in 65.1 in | | | | |
| Hip Room: | 60.8 in 60.3 in | | | | |
| <u>Interior Volume:</u> | | | | | |
| Front: | 63.8 cubic feet | | | | |
| Rear : | 56.9 cubic feet | | | | |
| Comb : | 120.7 cubic feet | | | | |
| <u>MAX. Cargo:</u> 111.8 cu ft. | | | | | |
| <u>ENGINE</u> | | <u>DRIVETRAIN</u> | | | |
| Naturally aspirated V-8 | | <u>Transmission</u> Model 6L80E. | | | |
| <u>Fuel delivery system:</u> SPFI | | 6 speed automatic with lockup torque converter | | | |
| <u>Cubic Inches:</u> | 325 | <u>Axle Ratio:</u> 3.08:1 (Rear | | | |
| <u>Displacement:</u> | 5.3 Liters | Wheel Drive with H/D | | | |
| <u>Compression Ratio:</u> | 9.9:1 | Locking Differential) | | | |
| <u>Horse Power:</u> | 355 bhp @ 5600 rpm | | | | |
| <u>Torque (SAE net):</u> | 383 lb. feet @ 4100 rpm | | | | |
| <u>Alternator:</u> | 160 amp | | | | |
| <u>Battery:</u> | 660 CCA Primary | | | | |
| | 730 CCA Auxiliary | | | | |
| <u>TEST RESULTS</u> | | | | | |
| <u>ACCELERATION</u> | | <u>BRAKING</u> | | <u>32 LAP HIGH SPEED</u> | |
| 0-30mph – 2.6 sec. | | *151.6 ft. @ 60 mph | | Average Lap Time –01:29.5 | |
| 0-60mph – 7.3 sec | | | | Average Speed - 59.06 | |
| 0-100mph – 19.3 sec | | | | | |
| 30-60mph - 5.2 sec | | | | <u>PURSUIT</u> | |
| 60-100mph – 12.0 sec | | | | Average Lap Time – 4:47.0 | |
| ¼ mile –15.7 sec @ 90.1 mph | | | | Average Speed - 32.6 | |

MAKE: 2015 Chevrolet**MODEL: Tahoe 4WD (9C1)****SALES CODE # CK15706**

| | | | | | | | | | |
|--|--|---|---------------------------------------|-----|--|--|--|-----|--|
| Vehicle Type: front-engine, rear wheel drive, 4 door utility, Police Package vehicle | | EPA | | | | TESTED | | | |
| | | CITY | | HWY | | CITY | | HWY | |
| | | 16 | | 23 | | MPG* | | | |
| | | | | | | | | | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | | | <u>CHASSIS</u> | | | |
| <u>SEATS:</u> Front: Cloth bucket, 6 way power, manual lumbar and recline Rear: Vinyl split-folding 60/40 Bench MEASUREMENTS: <div>FrontRear</div> Headroom: 42.8 in 38.7 in Legroom: 45.3 in 39.0 in Shoulder 64.8 in 65.1 in Hip Room: 60.8 in 60.3 in Interior Volume: Front 63.8 cubic feet Rear 56.9 cubic feet Comb 120.7 cubic feet MAX. Cargo 111.8 cu ft. | | Fuel Capacity: 98.0 Liters 26.0 Gallons GVWR: 7,100 lbs Wheelbase: 116 in Ground Clearance: 8.5 in Overall Length: 204 in Overall Height: 72.4 in | | | | <u>STEERING</u> Type: Electric Power Rack and Pinion Curb-to-curb: 39 feet <u>SUSPENSION</u> Front: Independent single coil over shock with stabilizer bar Rear: Multi-link with coil springs <u>WHEEL+TIRES</u> Wheel size/type: 17x7.5 steel Tire type: Goodyear RSA, P265/60R17, Load Rating 108, Speed Rating ‘V’ | | | |
| <u>ENGINE</u> Naturally aspirated V-8 Fuel delivery system: SPFI Cubic Inches: 325 Displacement: 5.3 Liters Compression Ratio: 9.9:1 Horse Power: 355 bhp @ 5600 rpm Torque (SAE net): 383 lb. feet @ 4100 rpm Alternator: 160 amp Battery: 660 CCA Primary 730 CCA Auxiliary | | <u>DRIVETRAIN</u> Transmission Model 6L80E. 6 speed automatic with lockup torque converter Axle Ratio: 3.08:1 (Rear Wheel Drive with H/D Locking Differential) | | | | <u>BRAKES</u> Heavy Duty 4 – wheel anti-lock font & rear disc with Vacuum boost Front: 13.0 inch vented disc Rear: 13.5 inch vented disc | | | |
| <u>TEST RESULTS</u> | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 3.4 sec. 0-60mph – 8.3 sec 0-100mph – 21.3 sec 30-60mph – 5.5 sec 60-100mph – 13.1 sec ¼ mile –16.7 sec @ 88.0 mph | | | <u>BRAKING</u> *154.8 ft. @ 60 mph | | | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:31.9 Average Speed - 57.48 <u>PURSUIT</u> Average Lap Time - 4:56.11 Average Speed - 31.6 | | | |

MAKE: 2015 Chevrolet**MODEL: Caprice V6 (9C1)****SALES CODE # 1EW19**

| Vehicle Type: front-engine, rear wheel drive, 5 - passenger, 4 door sedan, Police Package vehicle | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>18</td><td>26</td><td colspan="2">20 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 18 | 26 | 20 MPG* | | | | | | | | | | | | |
|---|---|---|-------------|---|--|---|-----------------|---------|---------|-----------------|---------|---------|------------------|---------|---------|--------------|-----------------|-------------|-----------------|-------------|----------------|--------------|-----------------|---|---|--|
| EPA | | TESTED | | | | | | | | | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | | | | | | | | | |
| 18 | 26 | 20 MPG* | | | | | | | | | | | | | | | | | | | | | | | | |
| <p><u>INTERIOR</u></p> <p><u>SEATS:</u></p> <p>Front: Cloth bucket with high density foam, 8D/4P way power, manual lumbar</p> <p>Rear: Cloth bench</p> <p>MEASUREMENTS:</p> <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>38.7 in</td><td>37.6 in</td></tr><tr><td>Legroom:</td><td>42.2 in</td><td>43.2 in</td></tr><tr><td>Shoulder</td><td>59.1 in</td><td>59.0 in</td></tr><tr><td>Hip Room:</td><td>56.7 in</td><td>57.9 in</td></tr></table> <p>Interior Volume:</p> <table><tr><td>Front</td><td>56.0 cubic feet</td></tr><tr><td>Rear</td><td>56.0 cubic feet</td></tr><tr><td>Comb</td><td>112 cubic feet</td></tr><tr><td>Trunk</td><td>17.4 cubic feet</td></tr></table> | | Front | Rear | Headroom: | 38.7 in | 37.6 in | Legroom: | 42.2 in | 43.2 in | Shoulder | 59.1 in | 59.0 in | Hip Room: | 56.7 in | 57.9 in | Front | 56.0 cubic feet | Rear | 56.0 cubic feet | Comb | 112 cubic feet | Trunk | 17.4 cubic feet | <p><u>DIMENSIONS</u></p> <p>Fuel Capacity: 72.0 Liters 19.0 Gallons</p> <p>GVWR: 5,247 lb.</p> <p>Wheelbase: 118.5 in</p> <p>Ground Clearance: 5.6 in</p> <p>Overall Length: 204.2 in</p> <p>Overall Height: 58.7 in</p> | <p><u>CHASSIS</u></p> <p><u>STEERING</u> Type: Electrically assisted, Variable ratio, Rack and Pinion</p> <p>Curb-to-curb: 38 feet</p> <p><u>SUSPENSION</u></p> <p>Front: Independent strut, coil springs and stabilizer bar Rear: Independent strut, coil springs and stabilizer bar</p> <p><u>WHEEL+TIRES</u></p> <p>Wheel size/type: 8.0x18 steel, Tire type: Goodyear RSA P235/50R18, Load Rating 99, W Speed Rating</p> <p><u>BRAKES</u></p> <p>Power 4-Wheel anti-lock heavy duty disc, Police Calibration</p> <p>Front: 13.5 inch vented disc Rear: 12.7 inch vented disc</p> | |
| | Front | Rear | | | | | | | | | | | | | | | | | | | | | | | | |
| Headroom: | 38.7 in | 37.6 in | | | | | | | | | | | | | | | | | | | | | | | | |
| Legroom: | 42.2 in | 43.2 in | | | | | | | | | | | | | | | | | | | | | | | | |
| Shoulder | 59.1 in | 59.0 in | | | | | | | | | | | | | | | | | | | | | | | | |
| Hip Room: | 56.7 in | 57.9 in | | | | | | | | | | | | | | | | | | | | | | | | |
| Front | 56.0 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rear | 56.0 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | |
| Comb | 112 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | |
| Trunk | 17.4 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p><u>ENGINE</u></p> <p>Naturally aspirated V-6</p> <p>Fuel delivery system: SIDI</p> <p>Cubic Inches: 217</p> <p>Displacement: 3.6 Liters</p> <p>Compression Ratio: 11.3:1</p> <p>Horse Power: 301 bhp @ 6700 rpm</p> <p>Torque (SAE net): 265 lb. feet. @ 4800 rpm</p> <p>Alternator: 170 amp</p> <p>Battery: 700 CCA</p> | <p><u>DRIVETRAIN</u></p> <p>Transmission Model 6L80E. 6 speed automatic with lockup torque converter</p> <p>Axle Ratio: 2.92:1</p> | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p><u>TEST RESULTS</u></p> <table><tr><td><p><u>ACCELERATION</u></p><p>0-30mph – 2.7 sec.</p><p>0-60mph – 7.2 sec</p><p>0-100mph – 17.9 sec</p><p>30-60mph – 4.5 sec</p><p>60-100mph – 10.4 sec</p><p>¼ mile –15.5sec @ 92.4 mph</p></td><td><p><u>BRAKING</u></p><p>135.7 ft. @ 60 mph</p></td><td colspan="2"><p><u>32 LAP HIGH SPEED</u></p><p>Average Lap Time – 1:25.0</p><p>Average Speed - 62.02</p><p><u>PURSUIT</u></p><p>Average Lap Time - 4:35.00</p><p>Average Speed - 34.0</p></td></tr></table> | | | | <p><u>ACCELERATION</u></p> <p>0-30mph – 2.7 sec.</p> <p>0-60mph – 7.2 sec</p> <p>0-100mph – 17.9 sec</p> <p>30-60mph – 4.5 sec</p> <p>60-100mph – 10.4 sec</p> <p>¼ mile –15.5sec @ 92.4 mph</p> | <p><u>BRAKING</u></p> <p>135.7 ft. @ 60 mph</p> | <p><u>32 LAP HIGH SPEED</u></p> <p>Average Lap Time – 1:25.0</p> <p>Average Speed - 62.02</p> <p><u>PURSUIT</u></p> <p>Average Lap Time - 4:35.00</p> <p>Average Speed - 34.0</p> | | | | | | | | | | | | | | | | | | | | |
| <p><u>ACCELERATION</u></p> <p>0-30mph – 2.7 sec.</p> <p>0-60mph – 7.2 sec</p> <p>0-100mph – 17.9 sec</p> <p>30-60mph – 4.5 sec</p> <p>60-100mph – 10.4 sec</p> <p>¼ mile –15.5sec @ 92.4 mph</p> | <p><u>BRAKING</u></p> <p>135.7 ft. @ 60 mph</p> | <p><u>32 LAP HIGH SPEED</u></p> <p>Average Lap Time – 1:25.0</p> <p>Average Speed - 62.02</p> <p><u>PURSUIT</u></p> <p>Average Lap Time - 4:35.00</p> <p>Average Speed - 34.0</p> | | | | | | | | | | | | | | | | | | | | | | | | |

MAKE: 2015 Chevrolet**MODEL: Caprice V8 (9C1)****SALES CODE # 1EW19**

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------------|--|-------|--|-----------|---------|---------|----------|---------|---------|----------|---------|---------|-----------|---------|---------|-------|-----------------|------|-----------------|------|----------------|-------|-----------------|---|--|---|--|
| Vehicle Type: front-engine, rear wheel drive, 5 - passenger, 4 door sedan, Police Package vehicle | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | EPA | | TESTED | | | | | | | | | | | | | | | | | | | | | | | | |
| | | CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | | | | | | | | | |
| | | 15 | 24 | 16 MPG* | | | | | | | | | | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | <u>CHASSIS</u> | | | | | | | | | | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: Cloth bucket with high density foam, 8D/4P way power, manual lumbar Rear: Cloth bench MEASUREMENTS: <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>38.7 in</td><td>37.6 in</td></tr><tr><td>Legroom:</td><td>42.2 in</td><td>43.2 in</td></tr><tr><td>Shoulder</td><td>59.1 in</td><td>59.0 in</td></tr><tr><td>Hip Room:</td><td>56.7 in</td><td>57.9 in</td></tr></table> Interior Volume: <table><tr><td>Front</td><td>56.0 cubic feet</td></tr><tr><td>Rear</td><td>56.0 cubic feet</td></tr><tr><td>Comb</td><td>112 cubic feet</td></tr><tr><td>Trunk</td><td>17.4 cubic feet</td></tr></table> | | | Front | Rear | Headroom: | 38.7 in | 37.6 in | Legroom: | 42.2 in | 43.2 in | Shoulder | 59.1 in | 59.0 in | Hip Room: | 56.7 in | 57.9 in | Front | 56.0 cubic feet | Rear | 56.0 cubic feet | Comb | 112 cubic feet | Trunk | 17.4 cubic feet | Fuel Capacity: 72.0 Liters 19.0 Gallons GVWR: 5,357 lbs Wheelbase: 118.5 in Ground Clearance: 5.6 in Overall Length: 204.2 in Overall Height: 58.7 in | | <u>STEERING</u> Type: Electrically assisted, Variable ratio, Rack and Pinion Curb-to-curb : 38 feet <u>SUSPENSION</u> Front: Independent strut, coil springs and stabilizer bar Rear: Independent strut, coil springs and stabilizer bar <u>WHEEL+TIRES</u> Wheel size/type: 8.0x18 steel, Tire type: Goodyear RSA P235/50R18, Load Rating 99, W Speed Rating <u>BRAKES</u> Power 4-Wheel anti-lock heavy duty disc, Police Calibration Front: 13.5 inch vented disc Rear: 12.7 inch vented disc | |
| | Front | Rear | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Headroom: | 38.7 in | 37.6 in | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Legroom: | 42.2 in | 43.2 in | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Shoulder | 59.1 in | 59.0 in | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Hip Room: | 56.7 in | 57.9 in | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Front | 56.0 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rear | 56.0 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Comb | 112 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Trunk | 17.4 cubic feet | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <u>ENGINE</u> Naturally aspirated V-8 Fuel delivery system: SPFI Cubic Inches: 364 Displacement: 6.0 Liters Compression Ratio: 10.4:1 Horse Power: 355 bhp @ 5300 rpm Torque (SAE net): 384 lb. feet @ 4400 rpm Alternator: 170 amp Battery: 700 CCA | | <u>DRIVETRAIN</u> Transmission Model 6L80E. 6 speed automatic with lockup torque converter Axle Ratio: 2.92:1 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 2.7 sec. 0-60mph – 6.4 sec 0-100mph – 14.9 sec 30-60mph – 3.8 sec 60-100mph – 8.2 sec ¼ mile –14.9 sec @ 99.9 mph | | <u>BRAKING</u> 142.1 ft. @ 60 mph | | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:23.1 Average Speed - 63.41 <u>PURSUIT</u> Average Lap Time – 4:31.5 Average Speed - 34.5 | | | | | | | | | | | | | | | | | | | | | | | | |

MAKE: 2015 Dodge**MODEL: Charger V6 2.62****SALES CODE # 27A**

| | | | | | |
|--|--|---|-----|--|-----|
| Vehicle Type: Front engine, rear wheel drive, 5 passenger, 4 door sedan, police package vehicle. | | SALES CODE: 271 | | | |
| | | EPA | | TESTED | |
| | | CITY | HWY | CITY | HWY |
| | | 17 | 26 | 20 MPG* | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | <u>CHASSIS</u> | |
| <u>SEATS:</u> Front: Heavy duty cloth bucket Rear: Vinyl bench <u>MEASUREMENTS:</u> <div>FrontRear</div> Headroom: 38.6 in36.7 in Legroom: 41.8 in40.1 in Shoulder 59.5 in57.9 in Hip Room: 56.2 in56.1 in Interior Volume: Front: 55.6 cubic feet Rear: 49.3 cubic feet Comb: 104.9 cubic feet Trunk: 16.5 cubic feet | | Fuel Capacity: 18.5 Gallons GVWR: 5,250 lbs. Wheelbase: 120.0 in Ground Clearance: 5.2 in Overall Length: 200.1 in Overall Height: 58.2 in | | <u>STEERING</u> Type: Electric power assist rack and pinion Curb-to-curb: 38.9 ft. <u>SUSPENSION</u> Front: Independent high arm SLA with dual ball joint lower, coil spring and sway bar Rear: Independent multi-link, coil spring and swaybar | |
| <u>ENGINE</u> Naturally aspirated V-6 Fuel delivery system: SPFI Cubic Inches: 220 Displacement: 3.6 Liters Compression Ratio: 10.2:1 Horse Power: 292 @ 6400 RPM Torque (SAE net): 260 ft.lb @ 4400_RPM Alternator: 220 AMPS Battery: 800 CCA | | <u>DRIVETRAIN</u> Transmission: Model A580 5 speed automatic with overdrive and lockup torque converter Axle Ratio: 2.62:1 | | <u>WHEEL+TIRES</u> Wheel size/type: 18 x 7.5 Stl. Tire make: Goodyear Tire model: Eagle RS-A Tire Size: 245/55R18 Speed rating: V <u>BRAKES</u> Type: Power with dual piston front calipers, single piston rear calipers, anti-lock Front Disc : 388 sq. in. vented disc Rear Disc: 300 sq. in. vented disc | |
| <u>TEST RESULTS</u> | | | | | |
| <u>ACCELERATION</u> 0-30mph – 3.2 sec. 0-60mph – 7.8 sec 0-100mph – 20.1 sec 30-60mph – 5.0 sec 60-100mph – 11.8 sec ¼ mile –16.0 sec @ 92.1 mph | | <u>BRAKING</u> 133.3 ft. @ 60 mph | | <u>32 LAP HIGH SPEED</u> Average Lap Time –1:25.2 Average Speed - 61.91 <u>PURSUIT</u> Average Lap Time - 4:35.84 Average Speed - 33.9 | |

MAKE: 2015 Dodge**MODEL: Charger V6 3.07****SALES CODE # 29A**

| Vehicle Type: Front engine, rear wheel drive, 5 passenger, 4 door sedan, police package vehicle. | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>17</td><td>26</td><td colspan="2">20 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 17 | 26 | 20 MPG* | | | |
|---|---|---|------|-----------|---------|---------|----------|---------|---------|----------|---------|---------|-----------|---------|---------|---|---|
| EPA | | TESTED | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | |
| 17 | 26 | 20 MPG* | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | <u>DIMENSIONS</u> | <u>CHASSIS</u> | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: Heavy duty cloth bucket Rear: Vinyl bench <u>MEASUREMENTS:</u> <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>38.6 in</td><td>36.7 in</td></tr><tr><td>Legroom:</td><td>41.8 in</td><td>40.1 in</td></tr><tr><td>Shoulder</td><td>59.5 in</td><td>57.9 in</td></tr><tr><td>Hip Room:</td><td>56.2 in</td><td>56.1 in</td></tr></table> Interior Volume: Front: 55.6 cubic feet Rear: 49.3 cubic feet Comb: 104.9 cubic feet Trunk: 16.5 cubic feet | | Front | Rear | Headroom: | 38.6 in | 36.7 in | Legroom: | 41.8 in | 40.1 in | Shoulder | 59.5 in | 57.9 in | Hip Room: | 56.2 in | 56.1 in | Fuel Capacity: 18.5 Gallons GVWR: 5,250 lbs. Wheelbase: 120.0 in Ground Clearance: 5.2 in Overall Length: 200.1 in Overall Height: 58.2 in | <u>STEERING</u> Type: Electric power assist rack and pinion Curb-to-curb: 38.9 ft. <u>SUSPENSION</u> Front: Independent high arm SLA with dual ball joint lower, coil spring and sway bar Rear: Independent multi-link, coil spring and swaybar <u>WHEEL+TIRES</u> Wheel size/type: 18 x 7.5 Tire make: Goodyear Tire model: Eagle RS-A Tire Size: 245/55R18 Speed rating : V <u>BRAKES</u> Type: Power with dual piston front calipers, single piston rear calipers, anti-lock Front Disc : 388 sq. in. vented disc Rear Disc: 300 sq. in. vented disc |
| | Front | Rear | | | | | | | | | | | | | | | |
| Headroom: | 38.6 in | 36.7 in | | | | | | | | | | | | | | | |
| Legroom: | 41.8 in | 40.1 in | | | | | | | | | | | | | | | |
| Shoulder | 59.5 in | 57.9 in | | | | | | | | | | | | | | | |
| Hip Room: | 56.2 in | 56.1 in | | | | | | | | | | | | | | | |
| <u>ENGINE</u> | <u>DRIVETRAIN</u> | | | | | | | | | | | | | | | | |
| Naturally aspirated V-6 Fuel delivery system: SPFI Cubic Inches: 220 Displacement: 3.6 Liters Compression Ratio: 10.2:1 Horse Power: 292 @ 6400 RPM Torque (SAE net): 260 ft. lb. @ 4400 RPM Alternator: 220 AMPS Battery: 800 CCA | Transmission: Model A580 5 speed automatic with overdrive and lockup torque converter Axle Ratio: 3.08:1 | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 3.0 sec. 0-60mph – 7.7 sec 0-100mph – 19.8 sec 30-60mph – 5.0 sec 60-100mph – 11.7 sec ¼ mile –15.9sec @ 90.1 mph | <u>BRAKING</u> 134.4 ft. @ 60 mph | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:28.4 Average Speed - 59.71 <u>PURSUIT</u> Average Lap Time - 4:36.5 Average Speed - 33.8 | | | | | | | | | | | | | | | |

| Vehicle Type: Front engine, rear wheel drive, 5 passenger, 4 door sedan, police package vehicle. | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>15</td><td>25</td><td colspan="2">17 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 15 | 25 | 17 MPG* | | | | |
|---|--|---|-------------|--|--|---|-----------------|---------|---------|-----------------|---------|---------|------------------|---------|---------|--|--|--|
| EPA | | TESTED | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | |
| 15 | 25 | 17 MPG* | | | | | | | | | | | | | | | | |
| <p><u>INTERIOR</u></p> <p><u>SEATS:</u></p> <p>Front: Heavy duty cloth bucket Rear: Vinyl bench</p> <p><u>MEASUREMENTS:</u></p> <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>38.6 in</td><td>36.7 in</td></tr><tr><td>Legroom:</td><td>41.8 in</td><td>40.1 in</td></tr><tr><td>Shoulder</td><td>59.5 in</td><td>57.9 in</td></tr><tr><td>Hip Room:</td><td>56.2 in</td><td>56.1 in</td></tr></table> <p>Interior Volume: Front: 55.6 cubic feet Rear: 49.3 cubic feet Comb: 104.9 cubic feet Trunk: 16.5 cubic feet</p> | | Front | Rear | Headroom: | 38.6 in | 36.7 in | Legroom: | 41.8 in | 40.1 in | Shoulder | 59.5 in | 57.9 in | Hip Room: | 56.2 in | 56.1 in | <p><u>DIMENSIONS</u></p> <p>Fuel Capacity: 18.5 Gallons</p> <p>GVWR: 5,450 lbs.</p> <p>Wheelbase: 120.0 in</p> <p>Ground Clearance: 5.2 in</p> <p>Overall Length: 200.1 in</p> <p>Overall Height: 58.2 in</p> | <p><u>CHASSIS</u></p> <p><u>STEERING</u> Type: Electric power assist rack and pinion</p> <p>Curb-to-curb: 38.9 ft.</p> <p><u>SUSPENSION</u></p> <p>Front: Independent high arm SLA with dual ball joint lower, coil spring and sway bar</p> <p>Rear: Independent multi-link, coil spring and swaybar</p> <p><u>WHEEL+TIRES</u></p> <p>Wheel size/type: 18 x 7.5 Tire make: Goodyear Tire model: Eagle RS-A Tire Size: 245/55R18 Speed rating: V</p> <p><u>BRAKES</u> Type: Power with dual piston front calipers, single piston rear calipers, anti-lock</p> <p>Front Disc : 388 sq. in. vented disc Rear Disc: 300 sq. in. vented disc</p> | |
| | Front | Rear | | | | | | | | | | | | | | | | |
| Headroom: | 38.6 in | 36.7 in | | | | | | | | | | | | | | | | |
| Legroom: | 41.8 in | 40.1 in | | | | | | | | | | | | | | | | |
| Shoulder | 59.5 in | 57.9 in | | | | | | | | | | | | | | | | |
| Hip Room: | 56.2 in | 56.1 in | | | | | | | | | | | | | | | | |
| <p><u>ENGINE</u></p> <p>Naturally aspirated V-8</p> <p>Fuel delivery system: SPFI Cubic Inches: 345 Displacement: 5.7 Liters Compression Ratio: 10.5:1 Horse Power: 370 @ 5150 RPM Torque (SAE net): 397 ft. lb. @ 4250 RPM Alternator: 220 AMPS Battery: 800 CCA</p> | <p><u>DRIVETRAIN</u></p> <p>Transmission: Model A580 5 speed automatic with overdrive and lockup torque converter</p> <p>Axle Ratio: 2.62:1</p> | | | | | | | | | | | | | | | | | |
| <p><u>TEST RESULTS</u></p> <table><tr><td><p><u>ACCELERATION</u></p><p>0-30mph – 2.5 sec. 0-60mph – 6.0 sec 0-100mph – 14.5 sec 30-60mph – 3.8 sec 60-100mph – 8.5 sec ¼ mile –14.4 sec @ 99.9 mph</p></td><td><p><u>BRAKING</u></p><p>137.5 ft. @ 60 mph</p></td><td><p><u>32 LAP HIGH SPEED</u></p><p>Average Lap Time – 1:25.1 Average Speed - 61.98</p><p><u>PURSUIT</u></p><p>Average Lap Time - 4:32.82 Average Speed - 34.3</p></td></tr></table> | | | | <p><u>ACCELERATION</u></p> <p>0-30mph – 2.5 sec. 0-60mph – 6.0 sec 0-100mph – 14.5 sec 30-60mph – 3.8 sec 60-100mph – 8.5 sec ¼ mile –14.4 sec @ 99.9 mph</p> | <p><u>BRAKING</u></p> <p>137.5 ft. @ 60 mph</p> | <p><u>32 LAP HIGH SPEED</u></p> <p>Average Lap Time – 1:25.1 Average Speed - 61.98</p> <p><u>PURSUIT</u></p> <p>Average Lap Time - 4:32.82 Average Speed - 34.3</p> | | | | | | | | | | | | |
| <p><u>ACCELERATION</u></p> <p>0-30mph – 2.5 sec. 0-60mph – 6.0 sec 0-100mph – 14.5 sec 30-60mph – 3.8 sec 60-100mph – 8.5 sec ¼ mile –14.4 sec @ 99.9 mph</p> | <p><u>BRAKING</u></p> <p>137.5 ft. @ 60 mph</p> | <p><u>32 LAP HIGH SPEED</u></p> <p>Average Lap Time – 1:25.1 Average Speed - 61.98</p> <p><u>PURSUIT</u></p> <p>Average Lap Time - 4:32.82 Average Speed - 34.3</p> | | | | | | | | | | | | | | | | |

MAKE: 2015 Dodge**MODEL: Charger V8 3.06AWD****SALES CODE # 29A**

| Vehicle Type: Front engine, all-wheel drive, 5 passenger, 4 door sedan, police package vehicle. | | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>15</td><td>23</td><td colspan="2">16 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 15 | 23 | 16 MPG* | | | | | |
|---|---------|--|---|---|-----------|---------|---------|----------|---------|---------|----------|---------|---------|-----------|---------|---------|---|--|--|--|
| EPA | | TESTED | | | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | | | |
| 15 | 23 | 16 MPG* | | | | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | <u>CHASSIS</u> | | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: Heavy duty cloth bucket Rear: Vinyl bench <u>MEASUREMENTS:</u> <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>38.6 in</td><td>36.7 in</td></tr><tr><td>Legroom:</td><td>41.8 in</td><td>40.1 in</td></tr><tr><td>Shoulder</td><td>59.5 in</td><td>57.9 in</td></tr><tr><td>Hip Room:</td><td>56.2 in</td><td>56.1 in</td></tr></table> Interior Volume: Front: 55.6 cubic feet Rear: 49.3 cubic feet Comb: 104.9 cubic feet Trunk: 16.5 cubic feet | | | Front | Rear | Headroom: | 38.6 in | 36.7 in | Legroom: | 41.8 in | 40.1 in | Shoulder | 59.5 in | 57.9 in | Hip Room: | 56.2 in | 56.1 in | Fuel Capacity: 18.5 Gallons GVWR: 5,500 lbs. Wheelbase: 120.0 in Ground Clearance: 5.2 in Overall Length: 200.1 in Overall Height: 58.2 in | | <u>STEERING</u> Type: Power assist rack and pinion Curb-to-curb: 38.9 ft. <u>SUSPENSION</u> Front: Independent high arm SLA with dual ball joint lower, coil spring and sway bar Rear: Independent multi-link, coil spring and swaybar | |
| | Front | Rear | | | | | | | | | | | | | | | | | | |
| Headroom: | 38.6 in | 36.7 in | | | | | | | | | | | | | | | | | | |
| Legroom: | 41.8 in | 40.1 in | | | | | | | | | | | | | | | | | | |
| Shoulder | 59.5 in | 57.9 in | | | | | | | | | | | | | | | | | | |
| Hip Room: | 56.2 in | 56.1 in | | | | | | | | | | | | | | | | | | |
| <u>ENGINE</u> Naturally aspirated V-8 Fuel delivery system: SPFI Cubic Inches: 345 Displacement: 5.7 Liters Compression Ratio: 10.5:1 Horse Power: 370 @ 5150 RPM Torque (SAE net): 397 ft. lb. @ 4250 RPM Alternator: 220 AMPS Battery: 800 CCA | | <u>DRIVETRAIN</u> Transmission: Model A580 5 speed automatic with overdrive and lockup torque converter Axle Ratio: 3.08:1 | | <u>WHEEL+TIRES</u> Wheel size/type: 18 x 7.5 Tire make: Goodyear Tire model: Eagle RS-A Tire Size: 245/55R18 Speed rating: V <u>BRAKES</u> Type: Power with dual piston front calipers, single piston rear calipers, anti-lock Front Disc : 388 sq. in. vented disc Rear Disc: 300 sq. in. vented disc | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 2.5 sec. 0-60mph – 6.2 sec 0-100mph – 15.0 sec 30-60mph – 4.0 sec 60-100mph – 9.0 sec ¼ mile –14.8 sec @ 99.1 mph | | <u>BRAKING</u> 139.9 ft. @ 60 mph | | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:22.0 Average Speed - 64.32 <u>PURSUIT</u> Average Lap Time - 4:21.0 Average Speed - 35.9 | | | | | | | | | | | | | | | | |

MAKE: 2015 Ford**MODEL: PI FWD Sedan
SALES CODE # P2L**

| | | | | | | | | | | | | | | | | | | | | |
|--|---------|---|-------|--|-----------|---------|---------|----------|---------|---------|----------|---------|---------|-----------|---------|---------|---|--|--|--|
| Vehicle Type: front engine, front wheel drive, four door sedan, Police Package vehicle. | | <table><tr><td colspan="2">EPA</td><td colspan="2">TESTED</td></tr><tr><td>CITY</td><td>HWY</td><td>CITY</td><td>HWY</td></tr><tr><td>18</td><td>26</td><td colspan="2">19 MPG*</td></tr></table> | | | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 18 | 26 | 19 MPG* | | | | |
| EPA | | TESTED | | | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | | | |
| 18 | 26 | 19 MPG* | | | | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | <u>CHASSIS</u> | | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: Heavy duty cloth bucket, 6 way adjustable;4 way adjustable headrest Rear: Vinyl bench, Optional cloth bench MEASUREMENTS: <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>39.0 in</td><td>36.7 in</td></tr><tr><td>Legroom:</td><td>41.9 in</td><td>39.9 in</td></tr><tr><td>Shoulder</td><td>57.9 in</td><td>56.9 in</td></tr><tr><td>Hip Room:</td><td>56.3 in</td><td>55.9 in</td></tr></table> Interior Volume: Front: 54.8 cubic feet Rear: 48.1 cubic feet Comb: 103.0 cubic feet Trunk: 16.6 cubic feet | | | Front | Rear | Headroom: | 39.0 in | 36.7 in | Legroom: | 41.9 in | 39.9 in | Shoulder | 57.9 in | 56.9 in | Hip Room: | 56.3 in | 55.9 in | Fuel Capacity: 71.9 Liters 19.0 Gallons GVW: 5,460 lbs. Wheelbase: 112.9 in Ground Clearance: 6.0 in Length: 202.9 in Height: 61.3 in | | <u>STEERING</u> Electric power assist rack and pinion Curb-to-curb: 38.4 ft. <u>SUSPENSION</u> Front: Independent MacPherson strut with coil over shocks Rear: Multi-Link full independent <u>WHEEL+TIRES</u> Wheel size/type:18 x 8 Steel, 5 spoke Tire type: Goodyear 245/55R18 RS-A 103V <u>BRAKES</u> Power - dual piston calipers front, single piston calipers rear, 4 circuit and ABS Front: 13.9 inch vented disc Rear:13.6 inch vented disc | |
| | Front | Rear | | | | | | | | | | | | | | | | | | |
| Headroom: | 39.0 in | 36.7 in | | | | | | | | | | | | | | | | | | |
| Legroom: | 41.9 in | 39.9 in | | | | | | | | | | | | | | | | | | |
| Shoulder | 57.9 in | 56.9 in | | | | | | | | | | | | | | | | | | |
| Hip Room: | 56.3 in | 55.9 in | | | | | | | | | | | | | | | | | | |
| <u>ENGINE</u> Naturally aspirated V-6 Fuel Type: Gas Fuel delivery system: MPFI Cubic Inches: 214 Displacement: 3.5 Liters Compression Ratio: 10.8:1 Horse Power: 288 bhp @ 6500 rpm Torque (SAE net): 254 lb. feet @ 4000 rpm Alternator: 220 amp Battery: 750 CCA | | <u>DRIVETRAIN</u> Transmission: Model 6F50 6 speed electronic automatic with lockup torque converter Axle Ratio: 3.16:1 | | | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 3.1 sec. 0-60mph – 7.0 sec 0-100mph – 20.4 sec 30-60mph – 5.1 sec 60-100mph – 12.1 sec ¼ mile –16.2 sec @ 90.4 mph | | <u>BRAKING</u> 141.8 ft. @ 60 mph | | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:26.1 Average Speed - 61.21 <u>PURSUIT</u> Average Lap Time- 4:32.0 Average Speed - 34.4 | | | | | | | | | | | | | | | | |

MAKE: 2015 Ford**MODEL: PI AWD EcoBoost Sedan****SALES CODE # P2M 99T**

| Vehicle Type: front engine, Twin Turbo, all-wheel drive, four door sedan, Police Package vehicle... | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>16</td><td>23</td><td colspan="2">17 MPG*</td></tr></table> | | | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 16 | 23 | 17 MPG* | | | | |
|---|---------|---|-------|--|-----------|---------|---------|----------|---------|---------|----------|---------|---------|-----------|---------|---------|---|--|---|--|
| EPA | | TESTED | | | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | | | |
| 16 | 23 | 17 MPG* | | | | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | <u>CHASSIS</u> | | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: Heavy duty cloth bucket, 6 way poweradjustable;4 way adjustable headrest Rear: Vinyl bench, Optional cloth bench MEASUREMENTS: <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>39.0 in</td><td>36.7 in</td></tr><tr><td>Legroom:</td><td>41.9 in</td><td>39.9 in</td></tr><tr><td>Shoulder</td><td>57.9 in</td><td>56.9 in</td></tr><tr><td>Hip Room:</td><td>56.3 in</td><td>55.9 in</td></tr></table> Interior Volume: Front: 54.8 cubic feet Rear: 48.1 cubic feet Comb: 103.0 cubic feet Trunk: 16.6 cubic feet | | | Front | Rear | Headroom: | 39.0 in | 36.7 in | Legroom: | 41.9 in | 39.9 in | Shoulder | 57.9 in | 56.9 in | Hip Room: | 56.3 in | 55.9 in | Fuel Capacity: 72.0 Liters 19.0 Gallons GVW: 5,700 lbs. Wheelbase: 112.9 in Ground Clearance: 6.0 in Length: 202.9 in Height:61.3 in | | <u>STEERING</u> Electric power assist rack and pinion Curb-to-curb: 38.4 ft. <u>SUSPENSION</u> Front: Independent MacPherson strut with coil over shocks Rear: Multi-Link full independent <u>WHEEL+TIRES</u> Wheel size/type:18 x 8 Steel, 5 spoke Tire type: Goodyear 245/55R18 RS-A 103V | |
| | Front | Rear | | | | | | | | | | | | | | | | | | |
| Headroom: | 39.0 in | 36.7 in | | | | | | | | | | | | | | | | | | |
| Legroom: | 41.9 in | 39.9 in | | | | | | | | | | | | | | | | | | |
| Shoulder | 57.9 in | 56.9 in | | | | | | | | | | | | | | | | | | |
| Hip Room: | 56.3 in | 55.9 in | | | | | | | | | | | | | | | | | | |
| <u>ENGINE</u> | | <u>DRIVETRAIN</u> | | <u>BRAKES</u> | | | | | | | | | | | | | | | | |
| Twin turbo charged V-6 Fuel Type Gas Fuel delivery system: SDI Cubic Inches: 214 Displacement: 3.5 Liters Compression Ratio: 10.0:1 Horse Power: 365 bhp @ 5500 rpm Torque (SAE net): 350 lb.-ft. @ 1500-5250 rpm Alternator: 220 amp Battery: 750 CCA | | Transmission: Model 6F55 6 speed electronic automatic with lockup torque converter Axle Ratio: 3.16:1 with all- wheel drive | | Power - dual piston calipers front, single piston calipers rear, 4 circuit and ABS Front: 13.9 inch vented disc Rear:13.6 inch vented disc | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 2.4 sec. 0-60mph – 5.9 sec 0-100mph – 14.0 sec 30-60mph – 3.5 sec 60-100mph – 7.8sec ¼ mile –14.4 sec @ 101.6 mph | | <u>BRAKING</u> 143.1 ft. @ 60 mph | | <u>32 LAP HIGH SPEED</u> Average Lap Time –1:21.8 Average Speed - 64.53 <u>PURSUIT</u> Average Lap Time- 4:16.81 Average Speed - 36.5 | | | | | | | | | | | | | | | | |

MAKE: 2015 Ford**MODEL: PI AWD Sedan****SALES CODE # P2M, 99K**

| Vehicle Type: front engine, all-wheel drive, four door sedan, Police Package vehicle. | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>18</td><td>25</td><td colspan="2">19 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 18 | 25 | 19 MPG* | | | | |
|---|--|---|-------------|------------------|---------|---------|-----------------|---------|---------|-----------------|---------|----------|------------------|---------|---------|--|---|--|
| EPA | | TESTED | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | |
| 18 | 25 | 19 MPG* | | | | | | | | | | | | | | | | |
| <p><u>INTERIOR</u></p> <p><u>SEATS:</u></p> <p>Front: Heavy duty cloth bucket, 6 way poweradjustable;4 way adjustable headrest</p> <p>Rear: Vinyl bench, Optional cloth bench</p> <p>MEASUREMENTS:</p> <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>39.0 in</td><td>36.7 in</td></tr><tr><td>Legroom:</td><td>41.9 in</td><td>39.9 in</td></tr><tr><td>Shoulder</td><td>57.9 in</td><td>56.89 in</td></tr><tr><td>Hip Room:</td><td>56.3 in</td><td>55.9 in</td></tr></table> <p>Interior Volume:</p> <p>Front: 54.8 cubic feet</p> <p>Rear: 48.1 cubic feet</p> <p>Comb: 103.0 cubic feet</p> <p>Trunk: 16.6 cubic feet</p> | | Front | Rear | Headroom: | 39.0 in | 36.7 in | Legroom: | 41.9 in | 39.9 in | Shoulder | 57.9 in | 56.89 in | Hip Room: | 56.3 in | 55.9 in | <p><u>DIMENSIONS</u></p> <p>Fuel Capacity:</p> <p>71.9 Liters 19.0 Gallons</p> <p>GVW: 5,700 lbs.</p> <p>Wheelbase: 112.9 in</p> <p>Ground Clearance: 6.0 in</p> <p>Length: 202.9 in</p> <p>Height: 61.3 in</p> | <p><u>CHASSIS</u></p> <p><u>STEERING</u></p> <p>Electric power assist rack and pinion</p> <p>Curb-to-curb: 38.4 ft.</p> <p><u>SUSPENSION</u></p> <p>Front: Independent MacPherson strut with coil over shocks</p> <p>Rear: Multi-Link full independent</p> <p><u>WHEEL+TIRES</u></p> <p>Wheel size/type:18 x 8 Steel, 5 spoke</p> <p>Tire type: Goodyear 245/55R18 RS-A 103V</p> <p><u>BRAKES</u></p> <p>Power - dual piston calipers front, single piston calipers rear, 4 circuit and ABS</p> <p>Front: 13.9 inch vented disc</p> <p>Rear:13.6 inch vented disc</p> | |
| | Front | Rear | | | | | | | | | | | | | | | | |
| Headroom: | 39.0 in | 36.7 in | | | | | | | | | | | | | | | | |
| Legroom: | 41.9 in | 39.9 in | | | | | | | | | | | | | | | | |
| Shoulder | 57.9 in | 56.89 in | | | | | | | | | | | | | | | | |
| Hip Room: | 56.3 in | 55.9 in | | | | | | | | | | | | | | | | |
| <p><u>ENGINE</u></p> <p>Naturally aspirated V-6</p> <p>Fuel Type: Gas</p> <p>Fuel delivery system: MPFI</p> <p>Cubic Inches: 226</p> <p>Displacement: 3.7 Liters</p> <p>Compression Ratio: 10.5:1</p> <p>Horse Power: 305 bhp @ 6500 rpm</p> <p>Torque (SAE net): 279 lb.-ft. @ 4000 rpm</p> <p>Alternator: 220 amp</p> <p>Battery: 750 CCA</p> | <p><u>DRIVETRAIN</u></p> <p>Transmission: Model 6F50 6 speed electronic automatic with lockup torque converter</p> <p>Axle Ratio: 3.39:1 with all-wheel drive</p> | | | | | | | | | | | | | | | | | |
| <p><u>TEST RESULTS</u></p> | | | | | | | | | | | | | | | | | | |
| <p><u>ACCELERATION</u></p> <p>0-30mph – 3.0 sec.</p> <p>0-60mph – 7.9 sec</p> <p>0-100mph – 19.4 sec</p> <p>30-60mph – 5.0 sec</p> <p>60-100mph – 11.3 sec</p> <p>¼ mile –16.4 sec @ 91.5 mph</p> | <p><u>BRAKING</u></p> <p>141.6 ft. @ 60 mph</p> | <p><u>32 LAP HIGH SPEED</u></p> <p>Average Lap Time – 1:24.8</p> <p>Average Speed - 62.13</p> <p><u>PURSUIT</u></p> <p>Average Lap Time– 4:28.23</p> <p>Average Speed- 34.9</p> | | | | | | | | | | | | | | | | |

MAKE: 2015 Ford**MODEL: PI AWD Utility
SALES CODE # K8A,99R**

Vehicle Type: front engine, all-wheel drive, four door sport utility, Police Package vehicle.

| EPA | | TESTED | |
|------|-----|---------|-----|
| CITY | HWY | CITY | HWY |
| 16 | 21 | 17 MPG* | |

| <u>INTERIOR</u> | <u>DIMENSIONS</u> | <u>CHASSIS</u> | | | | | | | | | | | | | | | |
|---|---|--|-------------|------------------|---------|---------|-----------------|---------|---------|-----------------|--------|---------|------------------|---------|---------|--|---|
| <u>SEATS:</u> Front: Heavy duty cloth bucket, 6 way poweradjustable;4 way adjustable headrest Rear: Vinyl bench, 60/40 split MEASUREMENTS: <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>41.4 in</td><td>40.1 in</td></tr><tr><td>Legroom:</td><td>40.6 in</td><td>41.6 in</td></tr><tr><td>Shoulder</td><td>61.3in</td><td>60.9 in</td></tr><tr><td>Hip Room:</td><td>57.3 in</td><td>56.8 in</td></tr></table> Interior Volume: Front: 59.7 cubic feet Rear: 58.7 cubic feet Comb: 118.4 cubic feet Rear Cargo: 85.1 cubic feet | | Front | Rear | Headroom: | 41.4 in | 40.1 in | Legroom: | 40.6 in | 41.6 in | Shoulder | 61.3in | 60.9 in | Hip Room: | 57.3 in | 56.8 in | Fuel Capacity: 71.9 Liters 19.0 Gallons GVW: 6300 lbs. Wheelbase: 112.6 in Ground Clearance: 6.5 in Length: 197.1 in Height: 69.2 in (w/o roof rack) | <u>STEERING</u> Electronic power assist rack and pinion Curb-to-curb: 38.8 ft. <u>SUSPENSION</u> Front: Independent MacPherson strut with coil over shocks Rear: Multi-link full independent suspension <u>WHEEL+TIRES</u> Wheel size/type: 18 x 8 steel, 5 spoke Tire type: Goodyear Eagle 245/55R18 103V RS-A <u>BRAKES</u> Power with dual piston calipers front, single piston calipers rear, 4 circuit and ABS Front: 13.9 inch vented disc Rear: 13.6 inch vented disc |
| | Front | Rear | | | | | | | | | | | | | | | |
| Headroom: | 41.4 in | 40.1 in | | | | | | | | | | | | | | | |
| Legroom: | 40.6 in | 41.6 in | | | | | | | | | | | | | | | |
| Shoulder | 61.3in | 60.9 in | | | | | | | | | | | | | | | |
| Hip Room: | 57.3 in | 56.8 in | | | | | | | | | | | | | | | |
| <u>ENGINE</u> | <u>DRIVETRAIN</u> | | | | | | | | | | | | | | | | |
| Naturally aspirated V-6 Fuel Type Gas Fuel delivery system: MPFI Cubic Inches: 226 Displacement: 3.7 Liters Compression Ratio: 10.5:1 Horse Power: 304 bhp @ 6250 rpm Torque (SAE net): 279 lb.ft. @ 4000 rpm Alternator: 220 amp Battery: 750 CCA | Transmission: Model 6F55 6 speed electronic automatic with lockup torque converter Axle Ratio: 3.65:1 | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 2.9 sec. 0-60mph – 8.6 sec 0-100mph – 23.1 sec 30-60mph – 5.5 sec 60-100mph – 14.2 sec ¼ mile –16.5 sec @ 86.4 mph | <u>BRAKING</u> 141.4 ft. @ 60 mph | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:28.4 Average Speed - 59.71 <u>PURSUIT</u> Average Lap Time- 4:34.0 Average Speed - 34.2 | | | | | | | | | | | | | | | |

MAKE: 2015 Ford**MODEL: PI AWD EcoBoost Utility****SALES CODE # K8A,99R**

| Vehicle Type: front engine, all-wheel drive, four door sport utility, Police Package vehicle. | | | <table><tr><th colspan="2">EPA</th><th colspan="2">TESTED</th></tr><tr><th>CITY</th><th>HWY</th><th>CITY</th><th>HWY</th></tr><tr><td>15</td><td>20</td><td colspan="2">15 MPG*</td></tr></table> | | EPA | | TESTED | | CITY | HWY | CITY | HWY | 15 | 20 | 15 MPG* | | | | | |
|--|---------|---|---|---|-----------|---------|---------|----------|---------|---------|-----------|--------|---------|-----------|---------|---------|---|--|--|--|
| EPA | | TESTED | | | | | | | | | | | | | | | | | | |
| CITY | HWY | CITY | HWY | | | | | | | | | | | | | | | | | |
| 15 | 20 | 15 MPG* | | | | | | | | | | | | | | | | | | |
| <u>INTERIOR</u> | | <u>DIMENSIONS</u> | | <u>CHASSIS</u> | | | | | | | | | | | | | | | | |
| <u>SEATS:</u> Front: Heavy duty cloth bucket, 6 way power adjustable;4 way adjustable headrest Rear: Vinyl bench, 60/40 split MEASUREMENTS: <table><tr><td></td><td>Front</td><td>Rear</td></tr><tr><td>Headroom:</td><td>41.4 in</td><td>40.1 in</td></tr><tr><td>Legroom:</td><td>40.6 in</td><td>41.6 in</td></tr><tr><td>Shoulder:</td><td>61.3in</td><td>60.9 in</td></tr><tr><td>Hip Room:</td><td>57.3 in</td><td>56.8 in</td></tr></table> Interior Volume: Front: 59.7 cubic feet Rear: 58.7 cubic feet Comb: 118.4 cubic feet Rear Cargo: 85.1 cubic feet | | | Front | Rear | Headroom: | 41.4 in | 40.1 in | Legroom: | 40.6 in | 41.6 in | Shoulder: | 61.3in | 60.9 in | Hip Room: | 57.3 in | 56.8 in | Fuel Capacity: 71.9 Liters 19.0 Gallons GVW: 6300 lbs. Wheelbase: 112.6 in Ground Clearance: 6.5 in Length: 197.1 in Height: 69.2 in (w/o roof rack) | | <u>STEERING</u> Electronic power assist rack and pinion Curb-to-curb: 38.8 ft. <u>SUSPENSION</u> Front: Independent MacPherson strut with coil over shocks Rear: Multi-link full independent suspension <u>WHEEL+TIRES</u> Wheel size/type:18 x 8 steel, 5 spoke Tire type: Goodyear Eagle 245/55R18 103V RS-A <u>BRAKES</u> Power with dual piston calipers front, single piston calipers rear, 4 circuit and ABS Front: 13.9 inch vented disc Rear:13.6 inch vented disc | |
| | Front | Rear | | | | | | | | | | | | | | | | | | |
| Headroom: | 41.4 in | 40.1 in | | | | | | | | | | | | | | | | | | |
| Legroom: | 40.6 in | 41.6 in | | | | | | | | | | | | | | | | | | |
| Shoulder: | 61.3in | 60.9 in | | | | | | | | | | | | | | | | | | |
| Hip Room: | 57.3 in | 56.8 in | | | | | | | | | | | | | | | | | | |
| <u>ENGINE</u> Twin Turbocharged V-6 Fuel Type Gas Fuel delivery system: Direct Injection Cubic Inches: 214 Displacement: 3.5 Liters Compression Ratio: 10.0:1 Horse Power: 365 bhp @ 5550 rpm Torque (SAE net): 350 lb. ft. @ 1500-5250 rpm Alternator: 220 amp Battery: 750 CCA | | <u>DRIVETRAIN</u> Transmission: Model 6F55 6 speed electronic automatic with lockup torque converter Axle Ratio: 3.16:1 | | | | | | | | | | | | | | | | | | |
| <u>TEST RESULTS</u> | | | | | | | | | | | | | | | | | | | | |
| <u>ACCELERATION</u> 0-30mph – 2.5 sec. 0-60mph – 6.5 sec 0-100mph – 16.6 sec 30-60mph – 4.2 sec 60-100mph – 9.8 sec ¼ mile –15.0 sec @ 95.1 mph | | <u>BRAKING</u> 143.8 ft. @ 60 mph | | <u>32 LAP HIGH SPEED</u> Average Lap Time – 1:25.8 Average Speed - 61.54 <u>PURSUIT</u> Average Lap Time - 4:35.1 Average Speed - 34.0 | | | | | | | | | | | | | | | | |

32 LAP HIGH-SPEED VEHICLE DYNAMICS EVALUATION RESULTS

This test is conducted on a high-speed driving course. It is designed to evaluate, identify and eliminate the obviously unacceptable vehicles (i.e., those vehicles that are demonstrably unstable or otherwise exhibit unsafe characteristics).

For this test, four drivers are utilized for each vehicle. Each driver completes eight laps around our 1.46 mile test track at the AutoClub Speedway in Fontana, for a total of 32 timed laps. Lap timing is via a GPS based RaceLogic "DriftBox02" datalogger mounted in the vehicle. Lap times are immediately recorded via RF telemetry signal produced by the data logger. Secondary lap timing is recorded utilizing a "Video VBOX Datalogger" mounted in the vehicle. All timing is backed up on SD cards in each unit. The fastest and the slowest lap times are eliminated, the remaining six lap times are averaged. The average time and speed are recorded next to the driver's name.

Four Emergency Vehicle Operations Center driver training instructors, two each from the Los Angeles County Sheriff's Department and Los Angeles Police Department share the driving and evaluation of these vehicles.

At the conclusion of the preliminary handling portion of the test, each driver completes a "Driver's Subjective Evaluation" form. If the test vehicle is judged unacceptable in this preliminary review, it is rejected and not subject to further testing and evaluation.

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET IMPALA

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:28.14 | 1:27.24 | 1:27.62 | 1:28.64 | 1:28.74 | 1:28.74 | 1:28.53 | 1:28.79 | 1:28.41 | 59.7 |
| C. Dooros - LAPD | 1:29.44 | 1:28.38 | 1:29.18 | 1:29.00 | 1:29.15 | 1:29.35 | 1:28.93 | 1:29.08 | 1:29.13 | 59.1 |
| R. Juarez - LASD | 1:27.94 | 1:27.26 | 1:27.61 | 1:27.96 | 1:27.63 | 1:27.53 | 1:27.85 | 1:27.75 | 1:27.75 | 60.0 |
| A. Penrith - LAPD | 1:27.18 | 1:27.46 | 1:27.50 | 1:27.30 | 1:27.13 | 1:26.81 | 1:27.40 | 1:27.10 | 1:27.24 | 60.5 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 14:30 | 80/105 |
| C. Dooros - LAPD | 14:54 | 80/103 |
| R. Juarez - LASD | 15:30 | 81/103 |
| A. Penrith - LAPD | 15:50 | 80/102 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET IMPALA

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 8.7 |
| Body Lean | 8.1 |
| Bounce | 8.0 |
| Brake Fade | 9.6 |
| Brake Pull | 9.9 |
| ABS Operation | 10.0 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes –The brakes worked very well on all 8 laps with very good initial bite and very good rate of decel. Pedal travel was good and remained consistent in all 8 laps.</p> <p>Cornering/Handling – This car displayed neutral to moderate understeer in all corner. Body lean and bounce were not too bad but noticeable. The chassis is on the softer side of compliance.</p> <p>Transmission (Shift Points) – The transmission kept the engine within its power band without hunting for gears. The shift pattern was consistent in all 8 laps.</p> <p>Engine –The engine is a good strong power-plant, often too strong for the grip that is available.</p> <p>Other –It feels like front end is a little less compliant to road irregularities than optimum causes tires to skip and track out.</p> |

**32 LAP HIGH-SPEED COURSE
VEHICLE DYNAMICS EVALUATION
2015 CHEVROLET TAHOE PPV 2WD**

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-----------------|------------------|
| R. Robinson - LASD | 1:29.82 | 1:27.98 | 1:28.60 | 1:28.59 | 1:29.31 | 1:29.38 | 1:29.43 | 1:30.53 | 1:29:17 | 59.3 |
| C. Dooros - LAPD | 1:31.62 | 1:29.66 | 1:29.57 | 1:29.77 | 1:30.38 | 1:30.00 | 1:29.60 | 1:29.78 | 1:29.89 | 58.7 |
| R. Juarez - LASD | 1:30.13 | 1:28.76 | 1:28.91 | 1:28.58 | 1:28.58 | 1:29.05 | 1:28.75 | 1:29.24 | 1:28.91 | 59.4 |
| A. Penrith - LAPD | 1:32.37 | 1:29.02 | 1:30.36 | 1:29.81 | 1:29.58 | 1:29.55 | 1:30.57 | 1:30.13 | 1:29.99 | 58.8 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|--------------------------|---------------------------------------|
| R. Robinson - LASD | 12:26 | 76/100 |
| C. Dooros – LAPD | 12:49 | 76/100 |
| R. Juarez - LASD | 13:10 | 76/103 |
| A. Penrith - LAPD | 13:36 | 76/104 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET TAHOE PPV 2WD

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 8.7 |
| Body Lean | 8.2 |
| Bounce | 7.8 |
| Brake Fade | 9.5 |
| Brake Pull | 9.8 |
| ABS Operation | 7.7 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Brake worked well on all 8 laps, good confidence in breaking ability. If depressed firmly and quickly, one will get brake assist. No fade or ABS intrusion detected.</p> <p>Cornering/Handling – The vehicle displays neutral to moderate understeer in all turns depending on cornering speed. Stability / traction control was overly invasive if activated.</p> <p>Transmission (Shift Points) – The transmission worked well and shift points is consistent and predictable after few laps. There was no hunting for gears.</p> <p>Engine – The engine is strong and produced good consistent pull.</p> <p>Other – Tire slipping became apparent when the temperature rises.</p> |

**32 LAP HIGH-SPEED COURSE
VEHICLE DYNAMICS EVALUATION
2015 CHEVROLET CAPRICE V8 6.0L**

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-----------------|------------------|
| R. Robinson - LASD | 1:23.32 | 1:22.33 | 1:22.55 | 1:22.30 | 1:21.94 | 1:22.26 | 1:22.23 | 1:22.55 | 1:22.36 | 64.0 |
| C. Dooros - LAPD | 1:24.88 | 1:23.57 | 1:23.30 | 1:23.12 | 1:23.23 | 1:22.84 | 1:23.11 | 1:23.66 | 1:23.32 | 63.2 |
| R. Juarez - LASD | 1:23.59 | 1:23.10 | 1:22.82 | 1:22.59 | 1:23.34 | 1:22.52 | 1:23.14 | 1:23.35 | 1:23.05 | 63.4 |
| A. Penrith - LAPD | 1:24.74 | 1:25.70 | 1:23.49 | 1:23.51 | 1:22.97 | 1:23.46 | 1:23.49 | 1:23.83 | 1:23.75 | 63.0 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|--------------------------|---------------------------------------|
| R. Robinson - LASD | 10:23 | 74/85 |
| C. Dooros - LAPD | 10:43 | 71/85 |
| R. Juarez - LASD | 11:03 | 70/86 |
| A. Penrith - LAPD | 11:25 | 72/84 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET CAPRICE V8 6.0L

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.6 |
| Body Lean | 9.4 |
| Bounce | 9.7 |
| Brake Fade | 10 |
| Brake Pull | 9.8 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes –The brakes worked well in all 8 laps. Pedal feel and travel were very good, as was the rate of decel. However, slight pull is obvious during hard brake application.</p> <p>Cornering/Handling –This car displayed neutral to mild understeer handling characteristics. Steering and bounce were minimal.</p> <p>Transmission (Shift Points) –The transmission shift points were consistent and kept the engine within the power band.</p> <p>Engine –The engine is very strong and pulls extremely hard all through the power band. Good meshing of stability control with hard demand of vehicle-easy to modulate and drive.</p> |

**32 LAP HIGH-SPEED COURSE
VEHICLE DYNAMICS EVALUATION
2015 CHEVROLET CAPRICE V63.6L**

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-----------------|------------------|
| R. Robinson - LASD | 1:25.25 | 1:24.19 | 1:24.05 | 1:25.45 | 1:24.06 | 1:23.78 | 1:24.79 | 1:24.47 | 1:24.47 | 62.5 |
| C. Dooros - LAPD | 1:26.58 | 1:25.24 | 1:25.12 | 1:24.40 | 1:24.78 | 1:25.28 | 1:25.19 | 1:25.59 | 1:25.19 | 61.7 |
| R. Juarez - LASD | 1:25.63 | 1:24.75 | 1:24.75 | 1:24.15 | 1:24.68 | 1:24.28 | 1:24.40 | 1:24.70 | 1:24.58 | 62.3 |
| A. Penrith - LAPD | 1:26.16 | 1:25.83 | 1:24.38 | 1:26.97 | 1:25.03 | 1:25.42 | 1:26.23 | 1:25.46 | 1:25.69 | 61.6 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|--------------------------|---------------------------------------|
| R. Robinson - LASD | 12:44 | 80/108 |
| C. Dooros – LAPD | 13:04 | 79/110 |
| R. Juarez - LASD | 13:25 | 81/111 |
| A. Penrith - LAPD | 13:45 | 81/111 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET CAPRICE V6 3.6L

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 8.5 |
| Body Lean | 9.0 |
| Bounce | 9.0 |
| Brake Fade | 9.7 |
| Brake Pull | 10 |
| ABS Operation | 9.7 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – The brakes worked very well on all laps. The rate of decal was excellent throughout the laps. Brake grab / modulation is on the shorter side, so when depressed fully, ABS is more apparent. Good confidence in the brakes.</p> <p>Cornering/Handling –The car displayed neutral to minimal understeer handling characteristics. Turn-in is quicker than expected. Body lean and bounce were minimal and steering feel was very well weighted.</p> <p>Transmission (Shift Points) – The transmission stayed in appropriate gear keeping the engine in its power-band.</p> <p>Engine –Good and strong power-plant. Pulled strong to redline but affected by intervention of stability control when severe pitch was introduced into chassis.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V6 3.6L 2.62 axle

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:25.70 | 1:24.82 | 1:25.16 | 1:24.32 | 1:24.18 | 1:25.94 | 1:25.39 | 1:25.27 | 1:25.11 | 62.0 |
| C. Dooros - LAPD | 1:26.18 | 1:25.60 | 1:25.56 | 1:25.23 | 1:25.41 | 1:25.46 | 1:25.52 | 1:25.98 | 1:25.59 | 61.5 |
| R. Juarez - LASD | 1:25.19 | 1:24.75 | 1:24.77 | 1:24.63 | 1:24.35 | 1:24.79 | 1:25.71 | 1:25.25 | 1:24.90 | 62.1 |
| A. Penrith - LAPD | 1:25.44 | 1:24.84 | 1:24.67 | 1:24.64 | 1:25.54 | 1:25.00 | 1:24.93 | 1:25.64 | 1:25.08 | 62.0 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 13:25 | 80/109 |
| C. Dooros - LAPD | 13:45 | 81/109 |
| R. Juarez - LASD | 14:05 | 80/106 |
| A. Penrith - LAPD | 14:25 | 80/106 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V6 3.6L 2.62 axle

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.0 |
| Body Lean | 9.0 |
| Bounce | 8.6 |
| Brake Fade | 9.8 |
| Brake Pull | 10 |
| ABS Operation | 9.2 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Brakes worked well on all 8 laps with very good pedal feel and travel. No brake pull or brake fade noticeable. However during one lap (back straight) one driver experienced car shudder after a late brake application and was unable to replicate the problem during the remaining lap.</p> <p>Cornering/Handling – Very tough chassis. Perhaps a bit too stiff. Car responds well to turn-in but mid-corner adjustments can be harder due to quick response setting. Good steering feel.</p> <p>Transmission (Shift Points) – The transmission kept the engine within its power band, and stayed in the appropriate gear. It was seamless and consistent.</p> <p>Engine – Very strong with smooth power delivery.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V8 5.7L 2.62 axle

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-----------------|------------------|
| R. Robinson - LASD | 1:24.43 | 1:24.24 | 1:23.37 | 1:24.78 | 1:24.28 | 125.12 | 1:24.27 | 1:25.00 | 1:24.50 | 62.4 |
| C. Dooros - LAPD | 1:25.57 | 1:24.24 | 1:24.76 | 1:24.81 | 1:25.30 | 1:24.90 | 1:25.36 | 1:25.61 | 1:25.09 | 61.9 |
| R. Juarez - LASD | 1:25.28 | 1:24.70 | 1:24.76 | 1:24.86 | 1:25.37 | 1:25.32 | 1:25.00 | 1:24.95 | 1:25.04 | 62.0 |
| A. Penrith - LAPD | 1:25.50 | 1:24.64 | 1:25.44 | 1:25.49 | 1:25.95 | 1:26.11 | 1:25.59 | 1:26.93 | 1:25.68 | 61.6 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|--------------------------|---------------------------------------|
| R. Robinson - LASD | 11:45 | 74/83 |
| C. Dooros – LAPD | 12:05 | 74/93 |
| R. Juarez - LASD | 12:26 | 76/100 |
| A. Penrith - LAPD | 12:49 | 76/100 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V8 5.7L 2.62 axle

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.6 |
| Body Lean | 9.7 |
| Bounce | 9.4 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – The brakes worked consistently well throughout the testing. Great rate of decal, good modulation, lots of confidence and consistency in its ability to slow down.</p> <p>Cornering/Handling – TRAC control kicks in too soon. The driver also experienced a great deal of stability / traction control intervention on all corners no matter how smooth the steering and the throttle is applied. The engine easily over powers the chassis causing wheel spin and subsequent intervention.</p> <p>Transmission (Shift Points) – The transmission kept the engine in its power band at all times.</p> <p>Engine – Pulls extremely hard without any hesitation.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHARGER V8 5.7L AWD 3.06 axle

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:22.09 | 1:21.05 | 1:21.11 | 1:21.13 | 1:21.44 | 1:21.27 | 1:21.55 | 1:21.97 | 1:21.41 | 64.8 |
| C. Dooros - LAPD | 1:23.39 | 1:21.73 | 1:22.12 | 1:22.65 | 1:22.23 | 1:21.82 | 1:22.45 | 1:22.68 | 1:22.35 | 64.0 |
| R. Juarez - LASD | 1:22.98 | 1:22.03 | 1:21.17 | 1:21.83 | 1:21.06 | 1:21.44 | 1:21.63 | 1:21.19 | 1:21.56 | 64.6 |
| A. Penrith - LAPD | 1:22.76 | 1:22.75 | 1:22.58 | 1:23.43 | 1:23.29 | 1:22.28 | 1:22.10 | 1:22.46 | 1:22.70 | 63.8 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 09:00 | 68/72 |
| C. Dooros - LAPD | 09:21 | 69/76 |
| R. Juarez - LASD | 09:40 | 70/77 |
| A. Penrith - LAPD | 11:03 | 72/84 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHARGER V8 5.7L AWD 3.06 axle

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.4 |
| Body Lean | 9.5 |
| Bounce | 9.0 |
| Brake Fade | 9.5 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – The brakes worked consistently well throughout the testing. Drivers noted a great rate of deceleration, as well as good modulation. There was no increase in pedal pressure or travel, and there was no fade or pull noted.</p> <p>Cornering/Handling – This car displayed neutral to mild over steer handling characteristics. Turn-in was good as was mid corner rotation steering was well weighted. Good chassis! However it exhibits some understeer when driven in hard to tight corner.</p> <p>Transmission (Shift Points) – Good consistent shifting point. The transmission kept the engine in its power band at all times.</p> <p>Engine – Pulls extremely hard, tons of usable torque which was complimented by the AWD</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN FWD 3.5L

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:26.59 | 1:25.55 | 1:25.74 | 1:25.88 | 1:26.32 | 1:26.50 | 1:27.56 | 1:26.42 | 1:26.25 | 61.1 |
| C. Dooros - LAPD | 1:27.04 | 1:26.82 | 1:26.39 | 1:26.24 | 1:26.01 | 1:25.68 | 1:26.25 | 1:25.76 | 1:26.26 | 61.0 |
| R. Juarez - LASD | 1:26.78 | 1:26.48 | 1:26.55 | 1:26.55 | 1:26.02 | 1:26.42 | 1:26.19 | 1:26.00 | 1:26.37 | 61.0 |
| A. Penrith - LAPD | 1:25.49 | 1:25.84 | 1:26.05 | 1:25.31 | 1:25.45 | 1:25.43 | 1:25.23 | 1:25.48 | 1:25.52 | 61.7 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 12:10 | 80/106 |
| C. Dooros - LAPD | 12:30 | 80/106 |
| R. Juarez - LASD | 12:50 | 80/105 |
| A. Penrith - LAPD | 13:10 | 80/103 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN FWD 3.5L

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.4 |
| Body Lean | 9.4 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes –The brakes worked well on all laps. Pedal feel and travel were very good and remained consistent allowing for easy modulation. No brake fades or brake pull experienced.</p> <p>Cornering/Handling –This car displayed neutral to minimal understeer handling characteristics in all turns. Body lean and bounce were minimal. Steering feel and turn-in were very good.</p> <p>Transmission (Shift Points) – Transmission operation is very good and consistent in all gear ratio.</p> <p>Engine –Strong throughout the laps.</p> <p>Other – Tires: Consistent and predictable.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN AWD 3.7L

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:26.24 | 1:23.98 | 1:24.51 | 1:24.84 | 1:26.16 | 1:24.33 | 1:24.58 | 1:25.86 | 1:25.04 | 62.0 |
| C. Dooros - LAPD | 1:25.12 | 1:24.26 | 1:24.62 | 1:24.80 | 1:24.52 | 1:24.68 | 1:24.67 | 1:25.56 | 1:24.73 | 62.1 |
| R. Juarez - LASD | 1:24.58 | 1:24.11 | 1:24.43 | 1:24.39 | 1:24.45 | 1:24.97 | 1:24.50 | 1:24.95 | 1:24.53 | 62.3 |
| A. Penrith - LAPD | 1:25.44 | 1:24.60 | 1:24.55 | 1:25.05 | 1:25.70 | 1:24.54 | 1:24.83 | 1:24.73 | 1:24.85 | 62.1 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 11:54 | 75/104 |
| C. Dooros - LAPD | 12:20 | 78/109 |
| R. Juarez - LASD | 12:47 | 78/108 |
| A. Penrith - LAPD | 13:04 | 79/110 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN AWD 3.7L

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 9.4 |
| Brake Fade | 9.6 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes –The brakes worked well on all laps. Pedal feel and travel were very good and remained consistent allowing for easy modulation. No brake fades or brake pull experienced.</p> <p>Cornering/Handling – This car displayed very neutral handling characteristics. Turn-in was good and mild corner rotation was very good. Steering feel was weighted well. Body lean and bounce were minimal.</p> <p>Transmission (Shift Points) – Transmission operation is very good and consistent in all gear ratio.</p> <p>Engine – Strong throughout the laps with good pairing to chassis.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN ECOBOOST AWD

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:21.19 | 1:20.44 | 1:20.49 | 1:21.26 | 1:21.32 | 1:20.69 | 1:21.29 | 1:20.87 | 1:20.94 | 65.2 |
| C. Dooros - LAPD | 1:23.32 | 1:21.85 | 1:22.13 | 1:22.69 | 1:22.30 | 1:22.61 | 1:22.34 | 1:22.12 | 1:22.36 | 64.0 |
| R. Juarez - LASD | 1:21.64 | 1:21.19 | 1:20.88 | 1:21.29 | 1:21.70 | 1:21.20 | 1:20.82 | 1:21.67 | 1:21.29 | 64.8 |
| A. Penrith - LAPD | 1:22.48 | 1:22.62 | 1:22.32 | 1:22.08 | 1:22.72 | 1:22.39 | 1:21.81 | 1:22.72 | 1:22.43 | 64.1 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 09:40 | 70/77 |
| C. Dooros - LAPD | 11:04 | 72/84 |
| R. Juarez - LASD | 10:23 | 74/85 |
| A. Penrith - LAPD | 10:43 | 71/85 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN ECOBOOST AWD

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.6 |
| Body Lean | 9.8 |
| Bounce | 9.8 |
| Brake Fade | 9.8 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – The brakes were consistent throughout this testing, with good grip. There was no fade or pull. Pedal travel was long. There were no issues with the ABS.</p> <p>Cornering/Handling – This vehicle has neutral handling characteristics, well balanced chassis with great rotation on turn in.</p> <p>Transmissions (Shift Points) – There were no concerns with the transmission function. It was consistent and did a good job keeping the engine in its power band.</p> <p>Engine – The engine in this vehicle is rated strong to very strong. It pulled hard and smooth to redline.</p> <p>Other – One rater felt the tires on this vehicle were slippery, but consistent in handling.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR UTILITYAWD 3.7L

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:27.88 | 1:27.88 | 1:27.85 | 1:27.63 | 1:27.64 | 1:27.70 | 1:28.00 | 1:28.00 | 1:27.78 | 60.1 |
| C. Dooros - LAPD | 1:29.30 | 1:28.20 | 1:28.54 | 1:28.89 | 1:29.12 | 1:28.79 | 1:29.09 | 1:28.96 | 1:28.89 | 59.3 |
| R. Juarez - LASD | 1:28.54 | 1:28.54 | 1:27.91 | 1:28.87 | 1:28.38 | 1:27.90 | 1:27.98 | 1:27.96 | 1:28.22 | 59.8 |
| A. Penrith - LAPD | 1:29.80 | 1:28.12 | 1:28.58 | 1:28.74 | 1:28.50 | 1:28.55 | 1:28.14 | 1:28.76 | 1:28.54 | 59.7 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 13:10 | 76/103 |
| C. Dooros - LAPD | 13:36 | 76/104 |
| R. Juarez - LASD | 13:56 | 76/106 |
| A. Penrith - LAPD | 14:14 | 76/104 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR UTILITY AWD 3.7L

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.9 |
| Body Lean | 10 |
| Bounce | 9.8 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes –The brakes worked extremely well consistently. There was no fade or pull. Modulation and rate of deceleration were good. ABS was not intrusive.</p> <p>Cornering/Handling –This vehicle had neutral to mild understeer characteristics. The chassis was well dampened and interacts very well with the powertrain. The vehicle takes corners with minimal predictable traction control intervention. It continues to perform well with mild or severe inputs. Body lean and bounce were minimal.</p> <p>Transmission (Shift Points) –The transmission kept the engine in its power band at all times. Shift points were consistent.</p> <p>Engine –The engine made good power and pulled well. There was no hesitation felt. The traction control intervention was seamless.</p> <p>Other – The tires performed well throughout the test and were noted as being “outstanding.”</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR ECOBOOST UTILITY AWD 3.5L

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:25.00 | 1:23.89 | 1:24.00 | 1:24.75 | 1:25.20 | 1:24.84 | 1:25.22 | 1:25.50 | 1:24.86 | 62.2 |
| C. Dooros - LAPD | 1:25.58 | 1:25.32 | 1:25.42 | 1:25.45 | 1:25.55 | 1:25.16 | 1:25.71 | 1:25.39 | 1:25.44 | 61.8 |
| R. Juarez - LASD | 1:24.04 | 1:24.48 | 1:25.63 | 1:25.74 | 1:27.19 | 1:28.16 | 1:27.91 | 1:27.97 | 1:26.05 | 61.3 |
| A. Penrith - LAPD | 1:26.81 | 1:25.61 | 1:25.95 | 1:25.87 | 1:26.42 | 1:27.08 | 1:28.80 | 1:28.40 | 1:26.76 | 60.9 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 11:03 | 70/86 |
| C. Dooros - LAPD | 11:25 | 72/84 |
| R. Juarez - LASD | 11:45 | 74/83 |
| A. Penrith - LAPD | 12:05 | 74/93 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD POLICE INTERCEPTOR ECOBOOST UTILITY AWD 3.5L

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.1 |
| Body Lean | 9.0 |
| Bounce | 9.4 |
| Brake Fade | 8.6 |
| Brake Pull | 9.8 |
| ABS Operation | 9.8 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Drivers did not notice any pull when braking, however, there was noticeable fade and long pedal travel. Rate of deceleration was definitely reduced.</p> <p>Cornering/Handling –Neutral to mild understeer was noted. There was minimal body lean and bounce during transitions. There seemed to be a loss of power steering and AWD at the fifth lap of the last set of 8.</p> <p>Transmission (Shift Points) – The transmission was good at keeping the engine within its power band. However, as noted above at the fifth lap of the last set of 8 there was a noticeable change in shift points.</p> <p>Engine –Good strong pulling until the lap noted above.</p> <p>Other – Tires seem slippery.</p> |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V6 3.07

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|----------|-----------|
| R. Robinson - LASD | 1:25.41 | 1:24.37 | 1:26.19 | 1:25.63 | 1:26.82 | 1:26.94 | 1:27.26 | 1:27.07 | 01:26.2 | 61.5 |
| A. Penrith - LAPD | 1:25.14 | 1:24.61 | 1:24.50 | 1:24.46 | 1:24.56 | 1:24.69 | 1:24.67 | 1:24.66 | 01:24.7 | 62.3 |
| R. Juarez - LASD | 1:24.77 | 1:24.05 | 1:26.27 | 1:24.16 | 1:24.69 | 1:24.24 | 1:24.86 | 1:24.47 | 01:24.7 | 62.4 |
| G Correa - LAPD | 1:25.90 | 1:24.43 | 1:24.91 | 1:25.50 | 1:25.20 | 1:25.87 | 1:26.56 | 1:25.11 | 01:25.4 | 61.8 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|-------------------|--------------------------------|
| R. Robinson - LASD | 13:56 | 76/106 |
| A. Penrith - LAPD | 14:14 | 76/106 |
| R. Juarez - LASD | 14:35 | 80/106 |
| C. Dooros – LAPD | 14:55 | 80/105 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 2015 DODGE CHARGER V6 3.07

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.9 |
| Body Lean | 9.9 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Drivers did not notice any pull when braking, however, there was noticeable loud metal noise heard coming from front suspension during laps 1 and 5 or 6.</p> <p>Cornering/Handling –Neutral to mild understeer was noted. There was minimal body lean and bounce during transitions. Steering feel was good.</p> <p>Transmission (Shift Points) – The transmission was good at keeping the engine within its power band. The shifting points are smooth and consistent.</p> <p>Engine –Pulled well to the red line. Good power-plant: felt no hesitation or inconsistency.</p> |

**32 LAP HIGH-SPEED COURSE
VEHICLE DYNAMICS EVALUATION
2015 CHEVROLET TAHOE PPV 4WD**

| DRIVER | LAP 1 | LAP 2 | LAP 3 | LAP 4 | LAP 5 | LAP 6 | LAP 7 | LAP 8 | AVG TIME | AVG SPEED |
|--------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|-----------------|------------------|
| R. Robinson - LASD | 1:31.96 | 1:30.14 | 1:30.26 | 1:30.83 | 1:32.37 | 1:32.12 | 1:31.50 | 1:32.32 | 01:31.9 | 57.8 |
| C. Dooros - LAPD | 1:33.38 | 1:31.34 | 1:32.39 | 1:32.46 | 1:33.01 | 1:32.44 | 1:31.92 | 1:33.38 | 01:32.1 | 57.1 |
| R. Juarez - LASD | 1:31.08 | 1:29.83 | 1:30.94 | 1:32.08 | 1:31.68 | 1:29.92 | 1:30.58 | 1:31.50 | 01:31.1 | 58.1 |
| G. Correa - LAPD | 1:33.53 | 1:32.70 | 1:32.12 | 1:31.98 | 1:32.49 | 1:33.10 | 1:32.68 | 1:32.39 | 01:32.5 | 57.1 |

| DRIVER | TIME TEST STARTED | AIR TEMP / TRACK TEMP (Deg. F) |
|--------------------|--------------------------|---------------------------------------|
| R. Robinson - LASD | 14:35 | 80/106 |
| A. Penrith - LAPD | 14:55 | 80/105 |
| R. Juarez - LASD | 15:17 | 80/102 |
| G. Correa - LAPD | 15:39 | 80/101 |

32 LAP HIGH-SPEED COURSE VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET TAHOE PPV 4WD

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 8.7 |
| Body Lean | 7.7 |
| Bounce | 6.5 |
| Brake Fade | 9.0 |
| Brake Pull | 8.7 |
| ABS Operation | 7.5 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Brakes worked well on all laps. There was no brake fade or pull noticed.</p> <p>Cornering/Handling – Body lean and bounce were moderate. Handling displayed neutral to moderate understeer with traction / stability control intervention calibrated far too aggressive. On third lap between the double apex (West End) and the bus stop turn, there was constant intervention.</p> <p>Transmission (Shift Points) – The transmission was good at keeping the engine within its power band.</p> <p>Engine – Engine pull strong to redline.</p> |

PURSUIT COURSE EVALUATION RESULTS

This test is for those vehicles equipped with a factory installed POLICE PACKAGE and identified by the manufacturer as pursuit vehicles. This evaluation is conducted on a closed 2.6 mile city street course which closely represents the environment most urban law enforcement agencies must contend with. The course has several straight-a-ways and consists of many right and left turns and obstacles in the roadway.

This is the final test during our road certification and the manufacturers, if they so choose, are allowed to rebuild the vehicle's brake system and replace tires prior to this test.

For this test, two drivers are utilized for each vehicle. Each driver completes two laps around the city pursuit course. Lap timing is via a GPS based Race Logic "DriftBox02" mounted in the car. The combined times of the two laps are recorded next to the driver's name.

If the test vehicle is unable to complete the course in less than 5 minutes, it is judged unacceptable for high speed law enforcement use.

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD PI SEDAN AWD 3.7L

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|-----------------------|------------|---------------|-------|
| Robert Robinson- LASD | 04:23.88 | 76° F / 93° F | 35.4 |
| Carrie Dooros - LAPD | 04:23.88 | 78° F / 93° F | 34.4 |
| Average Time | 04:28.23 | Average Speed | 34.9 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 10 |
| Body Lean | 10 |
| Bounce | 10 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps.</p> <p>Cornering/Handling – The car was very neutral in all turns. Steering very quick and correctly weighed</p> <p>Transmission (Shift Points) – Performed well throughout all laps.</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION 2015 CHEVROLET CAPRICE V6 2.62

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|---------------|-------|
| Carrie Dooros - LAPD | 04:40.00 | 76° F / 93° F | 33.4 |
| Robert Robinson - LASD | 04:31.00 | 78° F / 93° F | 34.5 |
| Average Time | 04:35.00 | Average Speed | 34.0 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9 |
| Body Lean | 9 |
| Bounce | 9 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Worked well on both laps. Easy to modulate and hard good feel. No fade or pull.</p> <p>Cornering/Handling – Very responsive</p> <p>Transmission (Shift Points) – Performed well throughout all laps.</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V6 2.62

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|----------------------|------------|---------------|-------|
| Ramiro Juarez - LASD | 04:41.71 | 77° F / 91° F | 33.2 |
| Gary Correa - LAPD | 04:29.97 | 75° F / 90° F | 34.7 |
| Average Time | 04:35.84 | Average Speed | 33.9 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 9.5 |
| Brake Fade | 9.5 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps. Easy to modulate and had good feel. No fade or pull experienced.</p> <p>Cornering/Handling – Handled very well</p> <p>Transmission (Shift Points) – Good strong pulling engine</p> <p>Engine – The engine made good power</p> <p>Other: Tires: Consistent and predictable</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION 2015 CHEVROLET TAHOE PPV 4WD

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|----------------|-------|
| Carrie Dooros - LAPD | 04:59.88 | 80° F / 100° F | 31.2 |
| Robert Robinson - LASD | 04:52.34 | 77° F / 96° F | 32.0 |
| Average Time | 04:56.11 | Average Speed | 31.6 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 9.5 |
| Brake Fade | 9.5 |
| Brake Pull | 9.5 |
| ABS Operation | 9.5 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps. Easy to modulate and had good feel. No fade or pull. One driver noted “Brake pedal seems too high”.</p> <p>Cornering/Handling – This car displayed minimal to moderate under steer in all turns.</p> <p>Transmission (Shift Points) – Performed well throughout all laps.</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION 2015 CHEVROLET IMPALA 9C1

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|---------------|-------|
| Carrie Dooros - LAPD | 04:39.31 | 75° F / 95° F | 33.5 |
| Robert Robinson - LASD | 04:35.73 | 75° F / 93° F | 34.0 |
| Average Time | 04:37.52 | Average Speed | 33.7 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9 |
| Body Lean | 9 |
| Bounce | 9 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Pedal travel feel was a little soft and travel was long but decal was still good.</p> <p>Cornering/Handling – This car displayed mild understeer in turns.</p> <p>Transmission (Shift Points) – Performed very well.</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V8 2.62

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|----------------------|------------|----------------|-------|
| Gary Correa - LAPD | 04:31.62 | 83° F / 105° F | 34.4 |
| Ramiro Juarez - LASD | 04:34.02 | 80° F / 100° F | 34.2 |
| Average Time | 04:32.82 | Average Speed | 34.3 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps. Easy to modulate and had good feel. No brake fade or pull experienced.</p> <p>Cornering/Handling – This car displayed minimal to moderate under steer in all turns. Steering was very quick and well balanced.</p> <p>Transmission (Shift Points) – Performed well throughout all laps.</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION 2015 FORD PI SEDAN AWD ECOBOOST

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|----------------------|------------|----------------|-------|
| Ramiro Juarez - LASD | 04:18.68 | 78° F / 98° F | 36.3 |
| Gary Correa - LAPD | 04:14.94 | 78° F / 102° F | 36.8 |
| Average Time | 04:16.81 | Average Speed | 36.5 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 10 |
| Body Lean | 10 |
| Bounce | 10 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps. Pedal travel is long. Rate of decel/ bite is on the lower end.</p> <p>Cornering/Handling – Very good chassis - predictable</p> <p>Transmission (Shift Points) – Very good and consistent shifting points.</p> <p>Engine – Pulls very hard to redline.</p> <p>Other – Tires: Worked well and predictable</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION 2015 CHEVROLET CAPRICE V8 9C1

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|----------------|-------|
| Carrie Dooros - LAPD | 04:35.00 | 84° F / 104° F | 34.0 |
| Robert Robinson - LASD | 04:28.00 | 84° F / 105° F | 34.9 |
| Average Time | 04:31.05 | Average Speed | 34.5 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 10 |
| Body Lean | 9.5 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps.</p> <p>Cornering/Handling – This car was neutral in turns</p> <p>Transmission (Shift Points) – Worked well on both laps</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD PI UTILITY AWD ECOBOOST

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|----------------|-------|
| Robert Robinson - LASD | 04:31.82 | 84° F / 104° F | 34.4 |
| Carrie Dooros - LAPD | 04:38.20 | 84° F / 105° F | 33.7 |
| Average Time | 04:35.05 | Average Speed | 34.0 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 10 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps but brake pedal travel seems long.</p> <p>Cornering/Handling – This car displayed minimal to moderate under steer in all turns. Very easy and smooth.</p> <p>Transmission (Shift Points) – Performed well throughout the laps.</p> <p>Engine – Strong and steady.</p> |

**PURSUIT COURSE
VEHICLE DYNAMICS EVALUATION
2015 DODGE CHARGER V8 3.06 AWD**

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|----------------------|------------|----------------|-------|
| Garry Correa - LAPD | 04:19.00 | 78° F / 98° F | 36.1 |
| Ramiro Juarez - LASD | 04:23.00 | 78° F / 102° F | 35.6 |
| Average Time | 04:21.00 | Average Speed | 35.9 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps. Very good, consistent and great confidence in stopping power.</p> <p>Cornering/Handling – Good chassis. Handled very well. However, it exhibit some understeer when driven in hard to tight corner.</p> <p>Transmission (Shift Points) – Good and consistent shifting points.</p> <p>Engine – Good: pulls extremely hard</p> |

PURSUIT COURSE

VEHICLE DYNAMICS EVALUATION

2015 CHEVROLET TAHOE PPV 2WD

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|----------------|-------|
| Robert Robinson - LASD | 04:45.00 | 80° F / 100° F | 32.8 |
| Carrie Dooros - LAPD | 04:49.00 | 77° F / 96° F | 32.4 |
| Average Time | 04:47.00 | Average Speed | 32.6 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 9.5 |
| Body Lean | 9.5 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on both laps.</p> <p>Cornering/Handling – This car displayed minimal to moderate under steer in all turns.</p> <p>Transmission (Shift Points) – Appropriate shifting points in all laps</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE

VEHICLE DYNAMICS EVALUATION

2015 FORD PI UTILITY AWD 3.7L

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|----------------------|------------|----------------|-------|
| Ramiro Juarez - LASD | 04:36.00 | 83° F / 105° F | 33.9 |
| Gary Correa - LAPD | 04:32.00 | 80° F / 100° F | 34.4 |
| Average Time | 04:34.00 | Average Speed | 34.2 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 10 |
| Body Lean | 10 |
| Bounce | 9.5 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|--|
| <p>Brakes – Worked well on all 8 laps. Good rate of decel- No issues with ABS, brake feel or pedal travel.</p> <p>Cornering/Handling – Great handling chassis, very well dampened. Good recovery from quick inputs, unfazed by rough driving inputs.</p> <p>Transmission (Shift Points) – Shifting points is consistent throughout the laps</p> <p>Engine – The engine made good power</p> <p>Other- Very well balanced vehicle. Great and consistent output. Well suited for Law Enforcement Agency!</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION

2015 DODGE CHARGER V6 3.07

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|------------------------|------------|---------------|-------|
| Robert Robinson - LASD | 04:37.00 | 75° F / 95° F | 33.8 |
| Carrie Dooros - LAPD | 04:36.00 | 75° F / 93° F | 33.9 |
| Average Time | 04:36.05 | Average Speed | 33.8 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 10 |
| Body Lean | 10 |
| Bounce | 10 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Worked well on both laps.</p> <p>Cornering/Handling – This car displayed mostly neutral handling.</p> <p>Transmission (Shift Points) – Performed well throughout the laps.</p> <p>Engine – The engine made good power</p> |

PURSUIT COURSE VEHICLE DYNAMICS EVALUATION

2015 FORD PI SEDAN FWD 3.5L

| DRIVERS | TOTAL TIME | AIR /TRACK | SPEED |
|----------------------|------------|---------------|-------|
| Carrie Dooros - LAPD | 04:28.00 | 77° F / 91° F | 34.9 |
| Ramiro Juarez - LASD | 04:36.00 | 75° F / 90° F | 33.9 |
| Average Time | 04:32.00 | Average Speed | 34.4 |

| ITEM | RATING ** |
|---------------|-----------|
| Steering | 10 |
| Body Lean | 10 |
| Bounce | 10 |
| Brake Fade | 10 |
| Brake Pull | 10 |
| ABS Operation | 10 |

** 1 – Poor 5 – Average 10 – Outstanding

| DRIVER COMMENTS |
|---|
| <p>Brakes – Worked well and consistent throughout both laps.</p> <p>Cornering/Handling – Good chassis. Car reacts in great sync to all inputs-very compliant and predictable</p> <p>Transmission (Shift Points) – Good consistent shift point.</p> <p>Engine – The engine made good power, pulled hard to redline.</p> <p>Other: Tires: Consistent and predictable</p> |

BRAKE EVALUATION RESULTS

This test procedure measures the braking response and efficiency of the vehicle.

The test is conducted immediately following the preliminary handling test (32 laps). This ensures that the brakes are tested after being driven at high speeds, thus simulating the actual operating conditions experienced by the officer in the field.

The test is conducted by first accelerating the vehicle to 80 MPH, then decelerating to a stop, maintaining an average deceleration rate of 22 feet per second. This procedure is repeated three additional times. At this point, a five minute stationary cool down period occurs. The vehicle is then accelerated to a speed of 60 MPH and decelerated at the maximum deceleration rate attainable before the onset of ABS. After a two minute stop, the 60 MPH procedure is repeated again. As soon as the vehicle has stopped, it is immediately accelerated to 60 MPH and then stopped as quickly as possible, simulating a panic stop. That stopping distance is measured and recorded, utilizing a "VBOX Datalogger". The "Datalogger" is a GPS based measuring device. If a brake malfunction is experienced (i.e., severe fading or inability to stop in a straight line,) an effort is made to detect the cause of the brake failure. If it is decided that the failure is inherent in the engineering of the brake system of the vehicle, the test is discontinued and the vehicle is disqualified from further testing. If the failure is associated with a correctable situation, it is corrected and the test is rerun. The defect and any remedial action taken are noted in the test results.

BRAKE TEST RESULTS

PANIC STOP FROM 60 MPH TO ZERO

| VEHICLE | STOPPING DISTANCE IN FEET CORRECTED TO 60 MPH |
|--|--|
| Chevrolet Impala 9C1 3.6L | 140.2ft @ 60MPH |
| Chevrolet Tahoe PPV 2WD | *151.6ft @ 60MPH |
| Chevrolet Tahoe PPV 4WD | *154.8ft @ 60MPH |
| Chevrolet Caprice V6 3.6L | 135.7ft @ 60MPH |
| Chevrolet Caprice V8 6.0L | 142.1ft @ 60MPH |
| Dodge Charger V6 2.62 | 133.3ft @ 60MPH |
| Dodge Charger V6 3.07 | 134.4ft @ 60MPH |
| Dodge Charger V8 2.62 | 137.5ft @ 60MPH |
| Dodge Charger V8 AWD 3.06 | 139.9ft @ 60MPH |
| Ford Police Interceptor Sedan FWD 3.5L | 141.8ft @ 60MPH |
| Ford Police Interceptor Sedan AWD 3.7L | 141.6ft @ 60MPH |
| Ford Police Interceptor Sedan AWD EcoBoost | 143.1ft @ 60MPH |
| Ford Police Interceptor Utility AWD 3.7L | 141.4ft @ 60MPH |
| Ford Police Interceptor Utility AWD EcoBoost | 143.8ft @ 60MPH |

*Vehicle was tested at later date after ABS software was updated: no brake parts were changed, 8 high speed laps were completed then brake test was performed with procedure listed on the protocol.

ACCELERATION EVALUATION RESULTS

This test is designed to measure vehicle performance in terms of acceleration, including speed and time elapsed at the quarter mile. Although the top speed is not recorded, a minimum of 100 MPH is generally obtained to satisfy the requirements for high speed law enforcement patrol.

To get the information on the 30 – 60 MPH and 60 – 100 MPH two separate runs were driven. In each run, the vehicle was accelerated to just under the target mileage. The vehicle's speed was allowed to level off, and then the vehicle was accelerated through the target mileage. This allowed for an actual time between the targeted mileages.

All of the information gathered during the acceleration and subsequent brake test is gathered using a Race Logic "Drift Box 02". The data logger is a GPS based measuring device.

ACCELERATION TEST RESULTS

| SPEED | CHEVROLET TAHOE PPV 2WD | CHEVROLET TAHOE PPV 4WD | CHEVROLET CAPRICE 3.6L | CHEVROLET CAPRICE 6.0L |
|---------------------|------------------------------------|------------------------------------|-----------------------------------|-----------------------------------|
| 0 – 20 MPH | 1.6 sec | 2.3 sec | 1.7 sec | 1.8 sec |
| 0 – 30 MPH | 2.6 sec | 3.4 sec | 2.7 sec | 2.7 sec |
| 0 – 40 MPH | 3.9 sec | 4.8 sec | 3.8 sec | 3.7 sec |
| 0 – 50 MPH | 5.6 sec | 6.5 sec | 5.5 sec | 5.0 sec |
| 0 – 60 MPH | 7.3 sec | 8.3 sec | 7.2 sec | 6.4 sec |
| 0 – 70 MPH | 9.8 sec | 11.0 sec | 9.0 sec | 8.3 sec |
| 0 – 80 MPH | 12.7 sec | 14.1 sec | 11.7 sec | 10.3 sec |
| 0 – 90 MPH | 15.7 sec | 17.3 sec | 14.8 sec | 12.5 sec |
| 0 – 100 MPH | 19.3 sec | 21.2sec | 17.9 sec | 14.9 sec |
| | | | | |
| 30 – 60 MPH | 5.2 sec | 5.5 sec | 4.5 sec | 3.8 sec |
| 60 – 100 MPH | 12.0 sec | 13.1 sec | 10.4 sec | 8.2 sec |
| *SS – ¼ Mile | 15.7 sec @ 90.1 mph | 16.7 sec @ 88.0 mph | 15.5 sec @ 92.4 mph | 14.9 sec @ 99.9 mph |

** Standing Start

| SPEED | CHEVROLET IMPALA 3.6L | FORD POLICE INTERCEPTOR FWD 3.5L | FORD POLICE INTERCEPTOR AWD 3.7L | FORD POLICE INTERCEPTOR ECOBOOST AWD |
|---------------------|----------------------------------|---|---|---|
| 0 – 20 MPH | 1.8 sec | 2.0 sec | 2.0 sec | 1.6 sec |
| 0 – 30 MPH | 2.9 sec | 3.1 sec | 3.0 sec | 2.4 sec |
| 0 – 40 MPH | 4.0 sec | 4.4 sec | 4.3 sec | 3.4 sec |
| 0 – 50 MPH | 5.5 sec | 5.9 sec | 5.8 sec | 4.4 sec |
| 0 – 60 MPH | 7.2 sec | 7.0 sec | 7.9 sec | 5.9 sec |
| 0 – 70 MPH | 9.0 sec | 10.5 sec | 10.1 sec | 7.5 sec |
| 0 – 80 MPH | 11.8 sec | 13.2 sec | 12.6 sec | 9.2 sec |
| 0 – 90 MPH | 15.0 sec | 16.1 sec | 15.6 sec | 11.5 sec |
| 0 – 100 MPH | 18.4 sec | 20.4 sec | 19.4 sec | 14.0 sec |
| | | | | |
| 30 – 60 MPH | 4.3 sec | 5.1 sec | 4.9 sec | 3.5 sec |
| 60 – 100 MPH | 11.4 sec | 12.1 sec | 11.3 sec | 7.8 sec |
| *SS – ¼ Mile | 15.6 sec @ 91.9 mph | 16.2 sec @ 90.4 mph | 16.0 sec @ 91.4 mph | 14.4 sec @ 101.6 mph |

** Standing Start

ACCELERATION TEST RESULTS

| SPEED | FORD POLICE INTERCEPTOR AWD UTILITY 3.7L | FORD POLICE INTERCEPTOR ECOBOOST UTILITY | | |
|---------------------|---|---|--|--|
| 0 – 20 MPH | 1.8 sec | 1.6 sec | | |
| 0 – 30 MPH | 3.0 sec | 2.5 sec | | |
| 0 – 40 MPH | 4.2 sec | 3.5 sec | | |
| 0 – 50 MPH | 6.1 sec | 4.7 sec | | |
| 0 – 60 MPH | 8.6 sec | 6.5 sec | | |
| 0 – 70 MPH | 11.0 sec | 8.5 sec | | |
| 0 – 80 MPH | 14.0 sec | 10.6 sec | | |
| 0 – 90 MPH | 17.9 sec | 13.5 sec | | |
| 0 – 100 MPH | 23.1 sec | 16.6 sec | | |
| | | | | |
| 30 – 60 MPH | 5.5 sec | 4.2 sec | | |
| 60 – 100 MPH | 14.2 sec | 9.8 sec | | |
| *SS – ¼ Mile | 16.5 sec @ 86.4 mph | 15.0 sec @ 95.1 mph | | |

** Standing Start

| SPEED | DODGE CHARGER 3.6L V6 2.62 | DODGE CHARGER 3.6L V6 3.07 | DODGE CHARGER 5.7L V8 - 2.62 | DODGE CHARGER 5.7L V8 AWD 3.06 |
|---------------------|---------------------------------------|---------------------------------------|---|---|
| 0 – 20 MPH | 1.9 sec | 1.8 sec | 1.5 sec | 1.6 sec |
| 0 – 30 MPH | 3.2 sec | 3.0 sec | 2.5 sec | 2.5 sec |
| 0 – 40 MPH | 4.6 sec | 4.2 sec | 3.4 sec | 3.5 sec |
| 0 – 50 MPH | 6.0 sec | 5.7 sec | 4.6 sec | 4.9 sec |
| 0 – 60 MPH | 7.8 sec | 7.7 sec | 6.0 sec | 6.2 sec |
| 0 – 70 MPH | 10.1 sec | 9.7 sec | 7.5 sec | 7.9 sec |
| 0 – 80 MPH | 12.6 sec | 12.2 sec | 9.3 sec | 10.1 sec |
| 0 – 90 MPH | 15.3 sec | 15.8 sec | 11.9 sec | 12.5 sec |
| 0 – 100 MPH | 20.1 sec | 19.8 sec | 14.5 sec | 15.0 sec |
| | | | | |
| 30 – 60 MPH | 5.0 sec | 5.0 | 3.8 sec | 3.9 sec |
| 60 – 100 MPH | 11.8 sec | 11.7 sec | 8.5 sec | 9.0 sec |
| *SS – ¼ Mile | 16.0 sec @ 92.1 mph | 15.9 sec @ 90.1 mph | 14.4 sec @ 99.9mph | 14.8 sec @ 99.1 mph |

** Standing Start

HEAT EVALUATION RESULTS

Today's modern exhaust emission and computer monitored automobile is designed to operate at much higher temperatures than vehicles from the 1970's and 1980's. Scientific breakthroughs in metallurgy and lubrication compositions allow the modern engine to operate at temperatures formerly thought to be detrimental. A vehicle from the 1970 era usually exceeded 180 degrees under normal driving conditions and generally overheated at 212 degrees. Today, modern engines operate safely between 200 to 260 degrees. Our heat testing is a "PASS-FAIL" scenario and is based on manufacturer's allowable operating temperatures.

Heat from each engine component is measured by a diagnostic tool via the vehicles data link connector. Components not electronically monitored by the onboard computers are measured by means of a digital thermometer.

Measurements are taken at the conclusion of the 32 high speed laps. This process is accomplished in the following manner:

- | | |
|-----------------------|---|
| 1. Transmission Fluid | Measurement taken via DLC (data link connector). |
| 2. Engine Oil | Measurement taken via DLC (data link connector). |
| 3. Power Steering | The probe is inserted into the pump reservoir fluid. |
| 4. Radiator Coolant | Measurement taken via DLC (data link connector) |
| 5. Outside Air | Temperature is measured away from the vehicle and in direct sunlight. |

VEHICLE HEAT EVALUATION

2015 CHEVROLET IMPALA 9C1

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 302° F | 248 ° F | 302° F | 262° F |
| TESTED AT | 208° F | 210°F | 185°F | 199°F |

2015 CHEVROLET TAHOE 2WD

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 302° F | 248° F | 302° F | 262° F |
| TESTED AT | 239°F | 226°F | 202° F | 212°F |

2015 CHEVROLET TAHOE 4WD

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 298° F | N/A-Elec. | 262° F |
| TESTED AT | 248°F | 228°F | N/A-Elec. | 214°F |

2015 CHEVROLET CAPRICE 3.6L

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 298° F | N/A-Elec. | 262° F |
| TESTED AT | 239°F | 216°F | N/A-Elec. | 194°F |

2015 CHEVROLET CAPRICE 6.0L

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 298° F | N/A-Elec. | 262° F |
| TESTED AT | 255°F | 219°F | N/A-Elec. | 207°F |

VEHICLE HEAT EVALUATION

2015 DODGE CHARGER 5.7L V8 2.62

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 310° F | 284° F | N/A-Elec. | 260° F |
| TESTED AT | 230°F | 190°F | N/A-Elec. | 212°F |

2015 DODGE CHARGER 5.7LV8 AWD 3.06

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 310° F | 284° F | N/A-Elec. | 260° F |
| TESTED AT | 230°F | 213°F | N/A-Elec. | 217°F |

2015 DODGE CHARGER 3.6L V6 2.62

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 210°F | 197°F | N/A-Elec. | 208°F |

2015 DODGE CHARGER 3.6L V6 3.07

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 219°F | 199°F | N/A-Elec. | 210°F |

VEHICLE HEAT EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN FWD 3.5L

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 221°F | 235°F | N/A-Elec. | 193°F |

2015 FORD POLICE INTERCEPTOR SEDAN AWD 3.7L

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 234°F | 243°F | N/A-Elec. | 196°F |

2015 FORD POLICE INTERCEPTOR SEDAN AWD ECOBOOST

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 234°F | 223°F | N/A-Elec. | 188°F |

2015 FORD POLICE INTERCEPTOR UTILITY AWD 3.7L

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 238°F | 232°F | N/A-Elec. | 197°F |

2015 FORD POLICE INTERCEPTOR UTILITY AWD ECOBOOST

| | ENGINE OIL | TRANSMISSION OIL | POWER STEERING | RADIATOR |
|-------------------------------|------------|------------------|----------------|----------|
| MANUFACTURER'S RECOMMENDATION | 320° F | 275° F | N/A-Elec. | 262° F |
| TESTED AT | 237°F | 215°F | N/A-Elec. | 198°F |

COMMUNICATIONS EVALUATION RESULTS

The communications evaluation of each vehicle is conducted by technicians assigned to the Los Angeles County Sheriff's Department's Communications and Fleet Management Bureau. This evaluation concerns itself with the radio installation, the effect of radio operation on vehicle performance and the effect of the vehicle on radio performance.

The Electromagnetic Interference Susceptibility test is intended for use in the presence of electromagnetic fields resulting from use of public safety two-way radios.

Vehicle performance must not be affected in any way by transmissions from a radio and antenna installed in the vehicle and operating in any of the frequency ranges of 450 to 512 MHz, and having a radio frequency output no more than 50 watts. Vehicle performance shall not be affected by the presence of another vehicle equipped with the above described radio and operated next to the subject vehicle.

Radiated and conducted electromagnetic interference vehicle systems and accessories shall be designed to reduce interference with the use of public safety radio receivers or electronic sirens or sound amplifiers. The effective sensitivity of a receiver installed in the vehicle shall not be reduced by more than the amount tabulated below for each frequency band:

| FREQUENCY BAND | ALLOWABLE DEGRADATION |
|-----------------------|------------------------------|
| 450 to 512 MHz | 3 dB |

Degradation is the difference in effective receiver sensitivity measured with the vehicle engine and accessories turned off as compared to that measured with the engine and accessories turned on.

Sensitivity is measured in terms of the 12 dB Sinad signal as defined in EIA Standard RS-204. To determine effective sensitivity, the receiver is connected to the antenna through an isolating the connector which allows introduction of the signal generator through the isolated port. Comparative signal strength readings are then taken with and without the interference present.

COMMUNICATION NOISE EVALUATION

2015 CHEVROLET IMPALA

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 3dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -90dB | -92dB | 0dB |
| Engine Idle (No Acc.) | -90dB | -92dB | 0dB |
| Engine High RPM (No Acc.) | -90dB | -92dB | 0dB |
| Engine Idle W/Air | -90dB | -92dB | 0dB |
| Engine Idle W/ Lights | -90dB | -92dB | 0dB |
| Engine Idle W/Heater | -90dB | -92dB | 0dB |
| Engine Idle W/All Acc. | -90dB | -92dB | 0dB |
| Engine High RPM W/All Acc. | -90dB | -92dB | 0dB |

Also Tested: Monitored approx. 300 frequencies between 470 and 510 MHz. No spurious signal detected. Radio used XTS-3000 and XTS-5000 Portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 7 |
| Microphone | 7 |
| Electronic Siren | 7 |
| Dashboard Accessibility | |
| Radio Control Head | 7 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 5 |
| Speakers | 7 |
| Microphones | 6 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 9 |
| One Radio Installation | 8 |
| Two Radio Installation | 7 |
| Antenna Installation | 4 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 8 |
| Accommodation for Cables | 5 |
| Hidden Siren Installation | 6 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 – Outstanding

COMMUNICATION NOISE EVALUATION

2015 CHEVROLET TAHOE

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -89dB | -92dB | 1dB |
| Engine Idle (No Acc.) | -89dB | -92dB | 1dB |
| Engine High RPM (No Acc.) | -89dB | -92dB | 1dB |
| Engine Idle W/Air | -89dB | -92dB | 1dB |
| Engine Idle W/ Lights | -89dB | -92dB | 1dB |
| Engine Idle W/Heater | -89dB | -92dB | 1dB |
| Engine Idle W/All Acc. | -89dB | -92dB | 1dB |
| Engine High RPM W/All Acc. | -89dB | -92dB | 1dB |

Also Tested: Monitored approx. 300 frequencies between 470 and 510 MHz. No spurious signal detected. Radios used XTS-3000 and XTS-5000 Portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 5 |
| Microphone | 6 |
| Electronic Siren | 5 |
| Dashboard Accessibility | |
| Radio Control Head | 7 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 7 |
| Speakers | 7 |
| Microphones | 7 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 5 |
| One Radio Installation | 9 |
| Two Radio Installation | 9 |
| Antenna Installation | 5 |
| Computer Installation | 8 |
| Engine Accessibility | |
| Battery Terminal Connection | 5 |
| Accommodation for Cables | 5 |
| Hidden Siren Installation | 5 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 – Outstanding

COMMUNICATION NOISE EVALUATION

2015 CHEVROLET CAPRICE 3.6L V6

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -87dB | -92dB | 3dB |
| Engine Idle (No Acc.) | -87dB | -92dB | 3dB |
| Engine High RPM (No Acc.) | -87dB | -92dB | 3dB |
| Engine Idle W/Air | -87dB | -92dB | 3dB |
| Engine Idle W/ Lights | -87dB | -92dB | 3dB |
| Engine Idle W/Heater | -87dB | -92dB | 3dB |
| Engine Idle W/All Acc. | -87dB | -92dB | 3dB |
| Engine High RPM W/All Acc. | -87dB | -92dB | 3dB |

Also Tested: Monitored approx. 200 frequencies between 470 and 510MHz. Spurious signal detected. Interference 482.3000 using XTS-5000 Portable.

No spurious signal detected using XTS-3000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 6 |
| Microphone | 6 |
| Electronic Siren | 6 |
| Dashboard Accessibility | |
| Radio Control Head | 6 |
| Siren Console | 5 |
| Mobile Digital Terminal/Computer | 5 |
| Speakers | 5 |
| Microphones | 5 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 9 |
| One Radio Installation | 7 |
| Two Radio Installation | 5 |
| Antenna Installation | 5 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 8 |
| Accommodation for Cables | 5 |
| Hidden Siren Installation | 5 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 – Outstanding

COMMUNICATION NOISE EVALUATION

2015 CHEVROLET CAPRICE 6.0L V8

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -88dB | -92dB | 3dB |
| Engine Idle (No Acc.) | -88dB | -92dB | 3dB |
| Engine High RPM (No Acc.) | -88dB | -92dB | 3dB |
| Engine Idle W/Air | -88dB | -92dB | 3dB |
| Engine Idle W/ Lights | -88dB | -92dB | 3dB |
| Engine Idle W/Heater | -88dB | -92dB | 3dB |
| Engine Idle W/All Acc. | -88dB | -92dB | 3dB |
| Engine High RPM W/All Acc. | -88dB | -92dB | 3dB |

Also Tested: Monitored approx. 200 frequencies between 470 and 510MHz. Spurious signal detected. Interference 482.3000 using XTS-5000 Portable.

No spurious signal detected using XTS-3000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 5 |
| Microphone | 6 |
| Electronic Siren | 5 |
| Dashboard Accessibility | |
| Radio Control Head | 7 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 7 |
| Speakers | 5 |
| Microphones | 5 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 9 |
| One Radio Installation | 7 |
| Two Radio Installation | 7 |
| Antenna Installation | 6 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 7 |
| Accommodation for Cables | 5 |
| Hidden Siren Installation | 5 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 – Outstanding

COMMUNICATION NOISE EVALUATION

2015 DODGE CHARGER 5.7L V8 2.62

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 3dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -90dBm | -94dBm | 2dBm |
| Engine Idle (No Acc.) | -88dBm | -92dBm | 4dBm |
| Engine High RPM (No Acc.) | -88dBm | -92dBm | 4dBm |
| Engine Idle W/Air | -87dBm | -92dBm | 4dBm |
| Engine Idle W/ Lights | -87dBm | -92dBm | 4dBm |
| Engine Idle W/Heater | -87dBm | -92dBm | 4dBm |
| Engine Idle W/All Acc. | -87dBm | -92dBm | 4dBm |
| Engine High RPM W/All Acc. | -88dBm | -92dBm | 4dBm |

Also Tested: Monitored approx. 300 frequencies.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 3 |
| Microphone | 4 |
| Electronic Siren | 5 |
| Dashboards Accessibility | |
| Radio Control Head | 6 |
| Siren Console | 6 |
| Mobile Digital Terminal/Computer | 5 |
| Speakers | 5 |
| Microphones | 5 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 8 |
| One Radio Installation | 6 |
| Two Radio Installation | 6 |
| Antenna Installation | 5 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 6 |
| Accommodation for Cables | 6 |
| Hidden Siren Installation | 6 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 – Outstanding

COMMUNICATION NOISE EVALUATION

2015 DODGE CHARGER 3.6L V6

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 3dB Gain Whip | Roof |

FREQUENCY: 482.8375 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -91dBm | -94dBm | 2dBm |
| Engine Idle (No Acc.) | -90dBm | -93dBm | 3dBm |
| Engine High RPM (No Acc.) | -90dBm | -93dBm | 3dBm |
| Engine Idle W/Air | -90dBm | -93dBm | 3dBm |
| Engine Idle W/ Lights | -90dBm | -93dBm | 3dBm |
| Engine Idle W/Heater | -90dBm | -93dBm | 3dBm |
| Engine Idle W/All Acc. | -90dBm | -93dBm | 3dBm |
| Engine High RPM W/All Acc. | -90dBm | -93dBm | 3dBm |

Also Tested: Monitored approx. 300 frequencies. No spurious signal detected. Radios used XTS-3000 and XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 3 |
| Microphone | 4 |
| Electronic Siren | 5 |
| Dashboard Accessibility | |
| Radio Control Head | 6 |
| Siren Console | 6 |
| Mobile Digital Terminal/Computer | 5 |
| Speakers | 5 |
| Microphones | 5 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 8 |
| One Radio Installation | 6 |
| Two Radio Installation | 6 |
| Antenna Installation | 5 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 6 |
| Accommodation for Cables | 6 |
| Hidden Siren Installation | 6 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 – Outstanding

COMMUNICATION NOISE EVALUATION

2015 DODGE CHARGER 5.7L AWD

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 3dB Gain Whip | Roof |

FREQUENCY: 482.8375 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -90dBm | -94dBm | 1dBm |
| Engine Idle (No Acc.) | -90dBm | -93dBm | 2dBm |
| Engine High RPM (No Acc.) | -90dBm | -93dBm | 2dBm |
| Engine Idle W/Air | -90dBm | -93dBm | 2dBm |
| Engine Idle W/ Lights | -90dBm | -93dBm | 2dBm |
| Engine Idle W/Heater | -90dBm | -93dBm | 2dBm |
| Engine Idle W/All Acc. | -90dBm | -93dBm | 2dBm |
| Engine High RPM W/All Acc. | -90dBm | -93dBm | 2dBm |

Also Tested: Monitored approx. 200 frequencies. Spurious signal detected at 484,000. Radios used XTS-3000 and XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 3 |
| Microphone | 4 |
| Electronic Siren | 5 |
| Dashboard Accessibility | |
| Radio Control Head | 6 |
| Siren Console | 6 |
| Mobile Digital Terminal/Computer | 5 |
| Speakers | 5 |
| Microphones | 5 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 8 |
| One Radio Installation | 6 |
| Two Radio Installation | 6 |
| Antenna Installation | 5 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 6 |
| Accommodation for Cables | 6 |
| Hidden Siren Installation | 6 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 - Outstanding

COMMUNICATION NOISE EVALUATION
2015 FORD POLICE INTERCEPTOR SEDAN
3.5L FWD

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 482.8375 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -90dB | -92dB | 0dB |
| Engine Idle (No Acc.) | -90dB | -92dB | 0dB |
| Engine High RPM (No Acc.) | -90dB | -92dB | 0dB |
| Engine Idle W/Air | -90dB | -92dB | 0dB |
| Engine Idle W/ Lights | -90dB | -92dB | 0dB |
| Engine Idle W/Heater | -90dB | -92dB | 0dB |
| Engine Idle W/All Acc. | -90dB | -92dB | 0dB |
| Engine High RPM W/All Acc. | -90dB | -92dB | 0dB |

Also Tested: Monitored approx. 200 frequencies. No spurious signal detected. Radios used XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 10 |
| Microphone | 10 |
| Electronic Siren | 9 |
| Dashboard Accessibility | |
| Radio Control Head | 10 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 4 |
| Speakers | 10 |
| Microphones | 9 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 1 |
| One Radio Installation | 6 |
| Two Radio Installation | 5 |
| Antenna Installation | 8 |
| Computer Installation | 6 |
| Engine Accessibility | |
| Battery Terminal Connection | 7 |
| Accommodation for Cables | 7 |
| Hidden Siren Installation | 7 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 - Outstanding

COMMUNICATION NOISE EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN

3.7L AWD

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -89dB | -92dB | 3dB |
| Engine Idle (No Acc.) | -89dB | -92dB | 3dB |
| Engine High RPM (No Acc.) | -89dB | -92dB | 3dB |
| Engine Idle W/Air | -89dB | -92dB | 3dB |
| Engine Idle W/ Lights | -89dB | -92dB | 3dB |
| Engine Idle W/Heater | -89dB | -92dB | 3dB |
| Engine Idle W/All Acc. | -89dB | -92dB | 3dB |
| Engine High RPM W/All Acc. | -89dB | -92dB | 3dB |

Also Tested: Monitored approx. 200 frequencies. No spurious signal detected.
Radios used XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 7 |
| Microphone | 7 |
| Electronic Siren | 7 |
| Dashboard Accessibility | |
| Radio Control Head | 5 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 7 |
| Speakers | 7 |
| Microphones | 7 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 1 |
| One Radio Installation | 7 |
| Two Radio Installation | 7 |
| Antenna Installation | 7 |
| Computer Installation | 7 |
| Engine Accessibility | |
| Battery Terminal Connection | 6 |
| Accommodation for Cables | 6 |
| Hidden Siren Installation | 7 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 6 |

** 1 – Poor 5 – Average 10 - Outstanding

COMMUNICATION NOISE EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN

3.5L AWD ECOBOOST

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 482.8375 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -87dB | -90dB | 3dB |
| Engine Idle (No Acc.) | -87dB | -90dB | 3dB |
| Engine High RPM (No Acc.) | -87dB | -90dB | 3dB |
| Engine Idle W/Air | -87dB | -90dB | 3dB |
| Engine Idle W/ Lights | -87dB | -90dB | 3dB |
| Engine Idle W/Heater | -87dB | -90dB | 3dB |
| Engine Idle W/All Acc. | -87dB | -90dB | 3dB |
| Engine High RPM W/All Acc. | -87dB | -90dB | 3dB |

Also Tested: Monitored approx. 200 frequencies. No spurious signal detected. Radios used XTS-3000 and XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 5 |
| Microphone | 5 |
| Electronic Siren | 5 |
| Dashboard Accessibility | |
| Radio Control Head | 6 |
| Siren Console | 6 |
| Mobile Digital Terminal/Computer | 6 |
| Speakers | 6 |
| Microphones | 5 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 1 |
| One Radio Installation | 5 |
| Two Radio Installation | 5 |
| Antenna Installation | 5 |
| Computer Installation | 5 |
| Engine Accessibility | |
| Battery Terminal Connection | 5 |
| Accommodation for Cables | 5 |
| Hidden Siren Installation | 6 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 5 |

** 1 – Poor 5 – Average 10 - Outstanding

COMMUNICATION NOISE EVALUATION

2015 FORD POLICE INTERCEPTOR UTILITY

3.7L AWD

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -89dB | -92dB | 3dB |
| Engine Idle (No Acc.) | -89dB | -92dB | 3dB |
| Engine High RPM (No Acc.) | -89dB | -92dB | 3dB |
| Engine Idle W/Air | -89dB | -92dB | 3dB |
| Engine Idle W/ Lights | -89dB | -92dB | 3dB |
| Engine Idle W/Heater | -89dB | -92dB | 3dB |
| Engine Idle W/All Acc. | -89dB | -92dB | 3dB |
| Engine High RPM W/All Acc. | -89dB | -92dB | 3dB |

Also Tested: Monitored approx. 300 frequencies between 470 and 510 MHz. Spurious signal detected at 470.875 and 470.6875. Radios used XTS-3000 and XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 6 |
| Microphone | 6 |
| Electronic Siren | 6 |
| Dashboard Accessibility | |
| Radio Control Head | 7 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 6 |
| Speakers | 6 |
| Microphones | 6 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 1 |
| One Radio Installation | 6 |
| Two Radio Installation | 6 |
| Antenna Installation | 6 |
| Computer Installation | 6 |
| Engine Accessibility | |
| Battery Terminal Connection | 6 |
| Accommodation for Cables | 6 |
| Hidden Siren Installation | 7 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 6 |

** 1 – Poor 5 – Average 10 - Outstanding

COMMUNICATION NOISE EVALUATION

2015 FORD POLICE INTERCEPTOR UTILITY

3.7L AWD ECOBOOST

| RADIO MAKE | MODEL NO. | ANTENNA TYPE | LOCATION |
|-------------------|--------------|---------------|----------|
| Motorola XTL-5000 | M20SSS9PW1AN | 5dB Gain Whip | Roof |

FREQUENCY: 483.0875 MHz

| WITH ANTENNA | 12 dB SINAD | 20 dB QUIETING | DESENS dB |
|----------------------------|-------------|----------------|-----------|
| Engine Off | -88dB | -91dB | 2dB |
| Engine Idle (No Acc.) | -88dB | -91dB | 2dB |
| Engine High RPM (No Acc.) | -88dB | -91dB | 2dB |
| Engine Idle W/Air | -88dB | -91dB | 2dB |
| Engine Idle W/ Lights | -88dB | -91dB | 2dB |
| Engine Idle W/Heater | -88dB | -91dB | 2dB |
| Engine Idle W/All Acc. | -88dB | -91dB | 2dB |
| Engine High RPM W/All Acc. | -88dB | -91dB | 2dB |

Also Tested: Monitored approx. 200 frequencies between 470 and 510 MHz. Spurious signal detected at 470.875. Radios used XTS-3000 and XTS-5000 portable.

| Glove Compartment Accessibility – (Undercover Use) | Rating ** |
|--|-----------|
| Control Head | 6 |
| Microphone | 6 |
| Electronic Siren | 6 |
| Dashboard Accessibility | |
| Radio Control Head | 7 |
| Siren Console | 7 |
| Mobile Digital Terminal/Computer | 6 |
| Speakers | 6 |
| Microphones | 6 |
| Trunk Accessibility | |
| Factory Power Terminal in Trunk | 1 |
| One Radio Installation | 6 |
| Two Radio Installation | 6 |
| Antenna Installation | 6 |
| Computer Installation | 6 |
| Engine Accessibility | |
| Battery Terminal Connection | 6 |
| Accommodation for Cables | 6 |
| Hidden Siren Installation | 7 |
| Ignition Fuse Terminal Block | |
| Clip – on Connections for Accessories | 6 |

** 1 – Poor 5 – Average 10 - Outstanding

ERGONOMICS

This subjective evaluation is a rating of human factors and space utilization done individually and independently by four patrol trained Deputy Sheriffs from the Los Angeles County Sheriff's Department. Each vehicle is driven through a 100 mile loop four times, each time by a different driver. The loop is divided equally into urban, suburban, and freeway driving conditions. The vehicle is operated with the air conditioner and headlights "turned on" and with the transmission selector in the overdrive position. No attempt is made to "baby" the vehicle through the loop, but hard acceleration starts are avoided. The ratings are averaged to minimize personal prejudices that individuals may have for, or against, any given vehicle.

Statements in the "drivers comment" section of the evaluation reflect a consensus of their individual comments.

Additionally, during the Ergonomics evaluation, fuel efficiency is also recorded. While EPA mileage estimates may be helpful for comparative purposes, they are based on simulated driving conditions. The fuel efficiency evaluation is an attempt to estimate MPG (miles per gallon) based on actual driving conditions.

The test results are averaged between the four drivers and recorded.

** 3 – Poor 5 – Average / Fair 6- Good 7-Very Good 8-Excellent

ERGONOMICS EVALUATION

2015 CHEVROLET IMPALA

| VISIBILITY | CONSIDERATIONS | RATING |
|---|---|--------|
| Overall Forward Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVERS COMMENTS | | |
| Windshield and window size were excellent | | |

| VISIBILITY | RATING USING MIRRORS | RATING NOT USING MIRRORS |
|------------------------------|----------------------|--------------------------|
| 3 o'clock Position | 5.8 | 5.8 |
| 4 o'clock Position | 5.2 | 5.2 |
| 5 o'clock Position | 5.4 | 5.4 |
| 6 o'clock Position | 5.4 | 5.4 |
| 7 o'clock Position | 5.4 | 5.4 |
| 8 o'clock Position | 5.4 | 5.4 |
| 9 o'clock Position | 5.8 | 5.8 |
| DRIVERS COMMENTS | | |
| Side mirrors are very small. | | |

| FRONT SEAT | CONSIDERATIONS | RATING |
|--|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 4.2 |
| Seat Position | Range of Adjustment | 5.4 |
| Seat Compatibility to Sam Brown | Comfort, Seatbelt Interference | 4.2 |
| Seat to Controls | Steering Wheel, Pedals, Dashboard | 5.4 |
| Headrest Position: With Hat/Helmet | Adequacy | 4.8 |
| Headrest Position: Without Hat/Helmet | Adequacy | 5.2 |
| Headroom | Adequacy | 5.4 |
| Legroom | Adequacy | 5.4 |
| Seatbelt | Ease of Hook-Up/Release | 5.4 |
| Shoulder Strap | Interference with duty gear | 5.4 |
| DRIVERS COMMENTS | | |
| Cabin feels tight causing gun interruption with the seat. Seat comfort was good for some drivers and not very good for others. | | |

| INSTRUMENT PANEL | CONSIDERATIONS | RATING |
|--|--|---------------|
| Instrument Placement | Ease of Viewing, Are They Obstructed by the Steering Wheel or Other Components | 5.4 |
| Instrument Visibility | Can You See Them | 6.4 |
| Instrument Legibility | Can You Read Them | 6.4 |
| DRIVERS COMMENTS | | |
| Instrument cluster placement is good, easy to read and understand. | | |

| CONTROLS | CONSIDERATIONS | RATING |
|--|---|---------------|
| Steering Wheel | Size, Position | 6 |
| Shift Lever | Accessibility, Indicator Visibility | 6 |
| Knobs & Switches | Location, Visibility, Markings, Arrangement | 6 |
| Pedals | Location | 6 |
| Pedals | Size | 6 |
| Pedals | Spacing (Do you hit more than one pedal with boots on?) | 6 |
| Parking Brake | Location | 6 |
| Parking Brake | Method of Release. | 6 |
| DRIVERS COMMENTS | | |
| All controls are user friendly and simple. | | |

| MIRRORS | CONSIDERATIONS | RATING |
|--|-----------------------|---------------|
| Rearview Mirror | Placement | 5.4 |
| Rearview Mirror | Size | 5.4 |
| Rearview Mirror | Ease of Adjustment | 5.4 |
| Rearview Mirror | Distortion | 5.4 |
| Driver Side Mirror | Placement | 5.4 |
| Driver Side Mirror | Size | 4.8 |
| Driver Side Mirror | Ease of Adjustment | 5.4 |
| Driver Side Mirror | Distortion | 4.8 |
| Passenger Side Mirror | Placement | 4.8 |
| Passenger Side Mirror | Size | 4.8 |
| Passenger Side Mirror | Ease of Adjustment | 5.4 |
| Passenger Side Mirror | Distortion | 5.4 |
| DRIVERS COMMENTS | | |
| Side view mirrors are easy to adjust and use while driving, but too small to view, loss of visibility, difficult to see very much. | | |

| DOORS | CONSIDERATIONS | RATING |
|--|----------------------------------|--------|
| Front Door | Ease of Ingress/Egress | 5.2 |
| Rear Door | Ease of Ingress/Egress | 5.2 |
| Window & Door Handles | Accessibility, Ease of Operation | 5.2 |
| DRIVERS COMMENTS | | |
| Small front doors, hard to get in / out with gear on. Handles and window controls easy to operate. | | |

| REAR SEAT | CONSIDERATIONS | RATING |
|---|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 5.2 |
| Headroom | Adequacy | 5.2 |
| Legroom | Adequacy | 5.2 |
| Seatbelt | Ease of Hook-Up/Release | 5.2 |
| DRIVERS COMMENTS | | |
| Seat comfort is bad. Entry/exit from rear doors a little difficult. | | |

| TRUNK | CONSIDERATIONS | RATING |
|---------------------------------|---------------------------|--------|
| Lid | Ease of Opening | 5.7 |
| Lid | Size of Opening | 6.7 |
| Compartment | Ease of Loading/Unloading | 6.7 |
| DRIVERS COMMENTS | | |
| Good size trunk, small opening. | | |

| SLALOM | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK - LEVEL | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.8 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK - INCLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| Back up camera | | |

| PARRALLEL PARK – DECLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

| REAR 3-POINT TURN | CONSIDERATIONS | RATING |
|-------------------------------|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

ERGONOMICS EVALUATION

2015 CHEVROLET TAHOE

| VISIBILITY | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Forward Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 8 |
| DRIVERS COMMENTS | | |
| | | |

| VISIBILITY | RATING USING MIRRORS | RATING NOT USING MIRRORS |
|--------------------|----------------------|--------------------------|
| 3 O'clock Position | 8 | 8 |
| 4 O'clock Position | 8 | 8 |
| 5 O'clock Position | 8 | 8 |
| 6 O'clock Position | 8 | 8 |
| 7 O'clock Position | 8 | 8 |
| 8 O'clock Position | 8 | 8 |
| 9 O'clock Position | 8 | 8 |
| DRIVERS COMMENTS | | |
| | | |

| FRONT SEAT | CONSIDERATIONS | RATING |
|---------------------------------------|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 7 |
| Seat Position | Range of Adjustment | 7 |
| Seat Compatibility to Sam Brown | Comfort, Seatbelt Interference | 5 |
| Seat to Controls | Steering Wheel, Pedals, Dashboard | 8 |
| Headrest Position: With Hat/Helmet | Adequacy | 8 |
| Headrest Position: Without Hat/Helmet | Adequacy | 8 |
| Headroom | Adequacy | 9 |
| Legroom | Adequacy, | 8 |
| Seatbelt | Ease of Hook-Up/Release | 7 |
| Shoulder Strap | Interference with duty gear | 6 |
| DRIVERS COMMENTS | | |
| | | |

| INSTRUMENT PANEL | CONSIDERATIONS | RATING |
|-------------------------|--|---------------|
| Instrument Placement | Ease of Viewing, Are They Obstructed by the Steering Wheel or Other Components | 7 |
| Instrument Visibility | Can You See Them | 7 |
| Instrument Legibility | Can You Read Them | 7 |
| DRIVERS COMMENTS | | |
| | | |

| CONTROLS | CONSIDERATIONS | RATING |
|-------------------------|---|---------------|
| Steering Wheel | Size, Position | 7 |
| Shift Lever | Accessibility, Indicator Visibility | 7 |
| Knobs & Switches | Location, Visibility, Markings, Arrangement | 7 |
| Pedals | Location | 7 |
| Pedals | Size | 7 |
| Pedals | Spacing (Do you hit more than one pedal with boots on?) | 7 |
| Parking Brake | Location | 7 |
| Parking Brake | Method of Release. | 6 |
| DRIVERS COMMENTS | | |
| | | |

| MIRRORS | CONSIDERATIONS | RATING |
|-------------------------|-----------------------|---------------|
| Rearview Mirror | Placement | 8 |
| Rearview Mirror | Size | 8 |
| Rearview Mirror | Ease of Adjustment | 8 |
| Rearview Mirror | Distortion | 8 |
| Driver Side Mirror | Placement | 8 |
| Driver Side Mirror | Size | 8 |
| Driver Side Mirror | Ease of Adjustment | 8 |
| Driver Side Mirror | Distortion | 8 |
| Passenger Side Mirror | Placement | 8 |
| Passenger Side Mirror | Size | 8 |
| Passenger Side Mirror | Ease of Adjustment | 8 |
| Passenger Side Mirror | Distortion | 8 |
| DRIVERS COMMENTS | | |
| | | |

| DOORS | CONSIDERATIONS | RATING |
|-----------------------|----------------------------------|--------|
| Front Door | Ease of Ingress/Egress | 7 |
| Rear Door | Ease of Ingress/Egress | 6 |
| Window & Door Handles | Accessibility, Ease of Operation | 6 |
| DRIVERS COMMENTS | | |
| | | |

| REAR SEAT | CONSIDERATIONS | RATING |
|------------------|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6 |
| Headroom | Adequacy | 6 |
| Legroom | Adequacy | 6 |
| Seatbelt | Ease of Hook-Up/Release | 6 |
| DRIVERS COMMENTS | | |
| | | |

| TRUNK | CONSIDERATIONS | RATING |
|------------------|---------------------------|--------|
| Lid | Ease of Opening | 8 |
| Lid | Size of Opening | 8 |
| Compartment | Ease of Loading/Unloading | 8 |
| DRIVERS COMMENTS | | |
| | | |

| SLALOM | CONSIDERATIONS | RATING |
|-------------------------------|--|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK - LEVEL | CONSIDERATIONS | RATING |
|-------------------------------|--|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK - INCLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK – DECLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

| REAR 3-POINT TURN | CONSIDERATIONS | RATING |
|-------------------------------|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| | | |

ERGONOMICS EVALUATION

2015 CHEVROLET CAPRICE

| VISIBILITY | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Forward Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.8 |
| DRIVERS COMMENTS | | |
| | | |

| VISIBILITY | RATING USING MIRRORS | RATING NOT USING MIRRORS |
|--|----------------------|--------------------------|
| 3 O'clock Position | 6.4 | 6.4 |
| 4 O'clock Position | 5.4 | 5.4 |
| 5 O'clock Position | 5.2 | 5.2 |
| 6 O'clock Position | 5.4 | 5.4 |
| 7 O'clock Position | 5.2 | 5.2 |
| 8 O'clock Position | 5.4 | 5.4 |
| 9 O'clock Position | 5.4 | 5.4 |
| DRIVERS COMMENTS | | |
| Good visibility right side. Left side has blind spots due to pillar placement. | | |

| FRONT SEAT | CONSIDERATIONS | RATING |
|--|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | |
| Seat Position | Range of Adjustment | 6.4 |
| Seat Compatibility to Sam Brown | Comfort, Seatbelt Interference | 6.4 |
| Seat to Controls | Steering Wheel, Pedals, Dashboard | 6.4 |
| Headrest Position: With Hat/Helmet | Adequacy | 6.4 |
| Headrest Position: Without Hat/Helmet | Adequacy | 6.4 |
| Headroom | Adequacy | 5.8 |
| Legroom | Adequacy | 6.4 |
| Seatbelt | Ease of Hook-Up/Release | 5.8 |
| Shoulder Strap | Interference with duty gear | 6.4 |
| DRIVERS COMMENTS | | |
| Seat is comfortable with duty gear, no pressure in lower back from handcuff case. Headroom is minimal for driver over 6 feet tall. | | |

| INSTRUMENT PANEL | CONSIDERATIONS | RATING |
|-------------------------|--|---------------|
| Instrument Placement | Ease of Viewing, Are They Obstructed by the Steering Wheel or Other Components | 6.2 |
| Instrument Visibility | Can You See Them | 6.2 |
| Instrument Legibility | Can You Read Them | 6.2 |
| DRIVERS COMMENTS | | |
| | | |

| CONTROLS | CONSIDERATIONS | RATING |
|--|---|---------------|
| Steering Wheel | Size, Position | 6.2 |
| Shift Lever | Accessibility, Indicator Visibility | 6.2 |
| Knobs & Switches | Location, Visibility, Markings, Arrangement | 6.2 |
| Pedals | Location | 6.2 |
| Pedals | Size | 6.2 |
| Pedals | Spacing (Do you hit more than one pedal with boots on?) | 6.2 |
| Parking Brake | Location | 6.2 |
| Parking Brake | Method of Release. | 6.2 |
| DRIVERS COMMENTS | | |
| All controls are within easy reach. Pedals placed comfortably but driver's floor area tight. Gear shift lever is too close to wiper control lever. | | |

| MIRRORS | CONSIDERATIONS | RATING |
|---|-----------------------|---------------|
| Rearview Mirror | Placement | 5.8 |
| Rearview Mirror | Size | 5.8 |
| Rearview Mirror | Ease of Adjustment | 5.8 |
| Rearview Mirror | Distortion | 5.8 |
| Driver Side Mirror | Placement | 5.8 |
| Driver Side Mirror | Size | 5.8 |
| Driver Side Mirror | Ease of Adjustment | 5.8 |
| Driver Side Mirror | Distortion | 5.8 |
| Passenger Side Mirror | Placement | 5.8 |
| Passenger Side Mirror | Size | 5.8 |
| Passenger Side Mirror | Ease of Adjustment | 5.8 |
| Passenger Side Mirror | Distortion | 5.8 |
| DRIVERS COMMENTS | | |
| Outside mirrors are too small and placed low. | | |

| DOORS | CONSIDERATIONS | RATING |
|-------------------------|----------------------------------|---------------|
| Front Door | Ease of Ingress/Egress | 5.6 |
| Rear Door | Ease of Ingress/Egress | 5.7 |
| Window & Door Handles | Accessibility, Ease of Operation | 5.8 |
| DRIVERS COMMENTS | | |
| | | |

| REAR SEAT | CONSIDERATIONS | RATING |
|-------------------------|---|---------------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6.2 |
| Headroom | Adequacy | 6.2 |
| Legroom | Adequacy | 6.2 |
| Seatbelt | Ease of Hook-Up/Release | 5.6 |
| DRIVERS COMMENTS | | |
| | | |

| TRUNK | CONSIDERATIONS | RATING |
|---|---------------------------|---------------|
| Lid | Ease of Opening | 6.2 |
| Lid | Size of Opening | 6.2 |
| Compartment | Ease of Loading/Unloading | 6.2 |
| DRIVERS COMMENTS | | |
| Deep trunk, plenty of space. Opening is a little small. | | |

| SLALOM | CONSIDERATIONS | RATING |
|--|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| Limited visibility due to large rear pillar. | | |

| PARRALLEL PARK - LEVEL | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6 |
| DRIVER COMMENTS | | |
| Limited visibility due to large pillar and small rear window. | | |

| PARRALLEL PARK - INCLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.6 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK – DECLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.6 |
| DRIVER COMMENTS | | |
| | | |

| REAR 3-POINT TURN | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.6 |
| DRIVER COMMENTS | | |
| Vehicle felt comfortable, had good turning radius, and was easy to turn. Some visibility issues with large rear pillar. | | |

ERGONOMICS EVALUATION

2015 DODGE CHARGER

| VISIBILITY | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Forward Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.6 |
| DRIVERS COMMENTS | | |
| | | |

| VISIBILITY | RATING USING MIRRORS | RATING NOT USING MIRRORS |
|--------------------|----------------------|--------------------------|
| 3 O'clock Position | 6.5 | 6.2 |
| 4 O'clock Position | 6.2 | 6.2 |
| 5 O'clock Position | 6.2 | 5.8 |
| 6 O'clock Position | 6.0 | 5.6 |
| 7 O'clock Position | 6.6 | 6.2 |
| 8 O'clock Position | 6.2 | 5.8 |
| 9 O'clock Position | 6.4 | 6.4 |
| DRIVERS COMMENTS | | |
| | | |

| FRONT SEAT | CONSIDERATIONS | RATING |
|---------------------------------------|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6.2 |
| Seat Position | Range of Adjustment | 6.8 |
| Seat Compatibility to Sam Brown | Comfort, Seatbelt Interference | 6.4 |
| Seat to Controls | Steering Wheel, Pedals, Dashboard | 6.4 |
| Headrest Position: With Hat/Helmet | Adequacy | 6.8 |
| Headrest Position: Without Hat/Helmet | Adequacy | 6.4 |
| Headroom | Adequacy | 6 |
| Legroom | Adequacy | 6 |
| Seatbelt | Ease of Hook-Up/Release | 6.2 |
| Shoulder Strap | Interference with duty gear | 6.2 |
| DRIVERS COMMENTS | | |
| | | |

| INSTRUMENT PANEL | CONSIDERATIONS | RATING |
|-------------------------|--|---------------|
| Instrument Placement | Ease of Viewing, Are They Obstructed by the Steering Wheel or Other Components | 5.7 |
| Instrument Visibility | Can You See Them | 6.4 |
| Instrument Legibility | Can You Read Them | 5.8 |
| DRIVERS COMMENTS | | |
| | | |

| CONTROLS | CONSIDERATIONS | RATING |
|-------------------------|---|---------------|
| Steering Wheel | Size, Position | 6.4 |
| Shift Lever | Accessibility, Indicator Visibility | 6.2 |
| Knobs & Switches | Location, Visibility, Markings, Arrangement | 6.0 |
| Pedals | Location | 6.4 |
| Pedals | Size | 6.4 |
| Pedals | Spacing (Do you hit more than one pedal with boots on?) | 6.0 |
| Parking Brake | Location | 6.2 |
| Parking Brake | Method of Release. | 6.2 |
| DRIVERS COMMENTS | | |
| | | |

| MIRRORS | CONSIDERATIONS | RATING |
|-------------------------|-----------------------|---------------|
| Rearview Mirror | Placement | 6.4 |
| Rearview Mirror | Size | 5.8 |
| Rearview Mirror | Ease of Adjustment | 6.4 |
| Rearview Mirror | Distortion | 6.0 |
| Driver Side Mirror | Placement | 6.4 |
| Driver Side Mirror | Size | 6.2 |
| Driver Side Mirror | Ease of Adjustment | 6.4 |
| Driver Side Mirror | Distortion | 6.0 |
| Passenger Side Mirror | Placement | 6.4 |
| Passenger Side Mirror | Size | 6.2 |
| Passenger Side Mirror | Ease of Adjustment | 6.4 |
| Passenger Side Mirror | Distortion | 6.0 |
| DRIVERS COMMENTS | | |
| | | |

| DOORS | CONSIDERATIONS | RATING |
|-----------------------|----------------------------------|--------|
| Front Door | Ease of Ingress/Egress | 6.2 |
| Rear Door | Ease of Ingress/Egress | 6.2 |
| Window & Door Handles | Accessibility, Ease of Operation | 6.4 |
| DRIVERS COMMENTS | | |
| | | |

| REAR SEAT | CONSIDERATIONS | RATING |
|------------------|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6.2 |
| Headroom | Adequacy | 6.2 |
| Legroom | Adequacy | 6.2 |
| Seatbelt | Ease of Hook-Up/Release | 5.8 |
| DRIVERS COMMENTS | | |
| | | |

| TRUNK | CONSIDERATIONS | RATING |
|------------------|---------------------------|--------|
| Lid | Ease of Opening | 5.4 |
| Lid | Size of Opening | 5.2 |
| Compartment | Ease of Loading/Unloading | 5.2 |
| DRIVERS COMMENTS | | |
| | | |

| SLALOM | CONSIDERATIONS | RATING |
|-------------------------------|--|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.2 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK - LEVEL | CONSIDERATIONS | RATING |
|-------------------------------|--|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.0 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK - INCLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.2 |
| DRIVER COMMENTS | | |
| | | |

| PARRALLEL PARK – DECLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.2 |
| DRIVER COMMENTS | | |
| | | |

| REAR 3-POINT TURN | CONSIDERATIONS | RATING |
|-------------------------------|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.2 |
| DRIVER COMMENTS | | |
| | | |

ERGONOMICS EVALUATION

2015 FORD POLICE INTERCEPTOR SEDAN

| VISIBILITY | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Forward Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.5 |
| DRIVERS COMMENTS | | |
| Overall visibility good. | | |

| VISIBILITY | RATING USING MIRRORS | RATING NOT USING MIRRORS |
|---|----------------------|--------------------------|
| 3 O'clock Position | 6 | 5.5 |
| 4 O'clock Position | 6 | 5.5 |
| 5 O'clock Position | 6 | 4.5 |
| 6 O'clock Position | 6 | 4.5 |
| 7 O'clock Position | 6 | 4.5 |
| 8 O'clock Position | 6 | 5.5 |
| 9 O'clock Position | 6 | 5.5 |
| DRIVERS COMMENTS | | |
| Limited visibility with no mirrors. Small rear window and high rear dash limit rear visibility. Convex (blind spot) mirrors are confusing and seem to be placed too high on the mirror. | | |

| FRONT SEAT | CONSIDERATIONS | RATING |
|---------------------------------------|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6.5 |
| Seat Position | Range of Adjustment | 8 |
| Seat Compatibility to Sam Brown | Comfort, Seatbelt Interference | 7 |
| Seat to Controls | Steering Wheel, Pedals, Dashboard | 7 |
| Headrest Position: With Hat/Helmet | Adequacy | 6.5 |
| Headrest Position: Without Hat/Helmet | Adequacy | 6.5 |
| Headroom | Adequacy | 6.5 |
| Legroom | Adequacy | 8 |
| Seatbelt | Ease of Hook-Up/Release | 6.5 |
| Shoulder Strap | Interference with duty gear | 6.5 |
| DRIVERS COMMENTS | | |
| Seat is comfortable. | | |

| INSTRUMENT PANEL | CONSIDERATIONS | RATING |
|--|--|---------------|
| Instrument Placement | Ease of Viewing, Are They Obstructed by the Steering Wheel or Other Components | 5.5 |
| Instrument Visibility | Can You See Them | 5.5 |
| Instrument Legibility | Can You Read Them | 5.5 |
| DRIVERS COMMENTS | | |
| Instrument placement and visibility is good. | | |

| CONTROLS | CONSIDERATIONS | RATING |
|---|---|---------------|
| Steering Wheel | Size, Position | 6 |
| Shift Lever | Accessibility, Indicator Visibility | 4.5 |
| Knobs & Switches | Location, Visibility, Markings, Arrangement | 6 |
| Pedals | Location | 6 |
| Pedals | Size | 6 |
| Pedals | Spacing (Do you hit more than one pedal with boots on?) | 6 |
| Parking Brake | Location | 6 |
| Parking Brake | Method of Release. | 6 |
| DRIVERS COMMENTS | | |
| Steering wheel has good fit/feel. Controls laid out well. Driver foot well area is tight when wearing boots. Pedal spacing is tight | | |

| MIRRORS | CONSIDERATIONS | RATING |
|---|-----------------------|---------------|
| Rearview Mirror | Placement | 6 |
| Rearview Mirror | Size | 5.5 |
| Rearview Mirror | Ease of Adjustment | 6 |
| Rearview Mirror | Distortion | 5.5 |
| Driver Side Mirror | Placement | 6 |
| Driver Side Mirror | Size | 6 |
| Driver Side Mirror | Ease of Adjustment | 6 |
| Driver Side Mirror | Distortion | 5.5 |
| Passenger Side Mirror | Placement | 6 |
| Passenger Side Mirror | Size | 5.5 |
| Passenger Side Mirror | Ease of Adjustment | 6 |
| Passenger Side Mirror | Distortion | 5.5 |
| DRIVERS COMMENTS | | |
| Mirror placement is good. Convex mirror placement can be confusing. | | |

| DOORS | CONSIDERATIONS | RATING |
|---|----------------------------------|--------|
| Front Door | Ease of Ingress/Egress | 7 |
| Rear Door | Ease of Ingress/Egress | 7 |
| Window & Door Handles | Accessibility, Ease of Operation | 6.5 |
| DRIVERS COMMENTS | | |
| Rear doors small, hard to enter. With prisoner cage installed the rear door ingress/egress may be very difficult. | | |

| REAR SEAT | CONSIDERATIONS | RATING |
|--|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6 |
| Headroom | Adequacy | 6 |
| Legroom | Adequacy | 6 |
| Seatbelt | Ease of Hook-Up/Release | 5.5 |
| DRIVERS COMMENTS | | |
| Minimal headroom in rear seat. Difficult ingress/egress. | | |

| TRUNK | CONSIDERATIONS | RATING |
|---|---------------------------|--------|
| Lid | Ease of Opening | 6 |
| Lid | Size of Opening | 6 |
| Compartment | Ease of Loading/Unloading | 6 |
| DRIVERS COMMENTS | | |
| Adequate trunk space, although shallow. | | |

| SLALOM | CONSIDERATIONS | RATING |
|--|---|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 4.5 |
| DRIVER COMMENTS | | |
| Visibility limited due to high rear dashboard and small windows. | | |

| PARRALLEL PARK - LEVEL | CONSIDERATIONS | RATING |
|----------------------------------|---|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.5 |
| DRIVER COMMENTS | | |
| Rear window has poor visibility. | | |

| PARRALLEL PARK - INCLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.5 |
| DRIVER COMMENTS | | |
| Average. | | |

| PARRALLEL PARK – DECLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.5 |
| DRIVER COMMENTS | | |
| Slightly better than incline. | | |

| REAR 3-POINT TURN | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 5.5 |
| DRIVER COMMENTS | | |
| Rear visibility hindered by small rear window and high rear dash. | | |

ERGONOMICS EVALUATION

2015 FORD POLICE INTERCEPTOR UTILITY

| VISIBILITY | CONSIDERATIONS | RATING |
|----------------------------|---|--------|
| Overall Forward Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 7 |
| DRIVERS COMMENTS | | |
| Good forward visibility. | | |

| VISIBILITY | RATING USING MIRRORS | RATING NOT USING MIRRORS |
|-------------------------|----------------------|--------------------------|
| 3 O'clock Position | 7.5 | 7.5 |
| 4 O'clock Position | 7.5 | 7.5 |
| 5 O'clock Position | 7.5 | 7.5 |
| 6 O'clock Position | 7.5 | 7.5 |
| 7 O'clock Position | 7.5 | 7.5 |
| 8 O'clock Position | 7.5 | 7.5 |
| 9 O'clock Position | 7.5 | 7.5 |
| DRIVERS COMMENTS | | |
| | | |

| FRONT SEAT | CONSIDERATIONS | RATING |
|--|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 6 |
| Seat Position | Range of Adjustment | 6 |
| Seat Compatibility to Sam Brown | Comfort, Seatbelt Interference | 5.7 |
| Seat to Controls | Steering Wheel, Pedals, Dashboard | 5.7 |
| Headrest Position: With Hat/Helmet | Adequacy | 5.7 |
| Headrest Position: Without Hat/Helmet | Adequacy | 5.7 |
| Headroom | Adequacy | 5.7 |
| Legroom | Adequacy | 7 |
| Seatbelt | Ease of Hook-Up/Release | 7 |
| Shoulder Strap | Interference with duty gear | 7 |
| DRIVERS COMMENTS | | |
| Seat is comfortable. Leg room may be limited for some drivers over 6 feet. | | |

| INSTRUMENT PANEL | CONSIDERATIONS | RATING |
|--|--|---------------|
| Instrument Placement | Ease of Viewing, Are They Obstructed by the Steering Wheel or Other Components | 6.7 |
| Instrument Visibility | Can You See Them | 6.7 |
| Instrument Legibility | Can You Read Them | 6.7 |
| DRIVERS COMMENTS | | |
| All instruments visible. Very good visibility. | | |

| CONTROLS | CONSIDERATIONS | RATING |
|-------------------------|---|---------------|
| Steering Wheel | Size, Position | 6.7 |
| Shift Lever | Accessibility, Indicator Visibility | 6.7 |
| Knobs & Switches | Location, Visibility, Markings, Arrangement | 6.7 |
| Pedals | Location | 6.7 |
| Pedals | Size | 6.7 |
| Pedals | Spacing (Do you hit more than one pedal with boots on?) | 6.7 |
| Parking Brake | Location | 6.7 |
| Parking Brake | Method of Release. | 6.7 |
| DRIVERS COMMENTS | | |
| | | |

| MIRRORS | CONSIDERATIONS | RATING |
|----------------------------------|-----------------------|---------------|
| Rearview Mirror | Placement | 5 |
| Rearview Mirror | Size | 5 |
| Rearview Mirror | Ease of Adjustment | 5 |
| Rearview Mirror | Distortion | 5 |
| Driver Side Mirror | Placement | 5 |
| Driver Side Mirror | Size | 5 |
| Driver Side Mirror | Ease of Adjustment | 5 |
| Driver Side Mirror | Distortion | 5 |
| Passenger Side Mirror | Placement | 5 |
| Passenger Side Mirror | Size | 6.7 |
| Passenger Side Mirror | Ease of Adjustment | 6.7 |
| Passenger Side Mirror | Distortion | 6.7 |
| DRIVERS COMMENTS | | |
| Larger mirrors would be helpful. | | |

| DOORS | CONSIDERATIONS | RATING |
|---|----------------------------------|--------|
| Front Door | Ease of Ingress/Egress | 6.6 |
| Rear Door | Ease of Ingress/Egress | 6.6 |
| Window & Door Handles | Accessibility, Ease of Operation | 6.6 |
| DRIVERS COMMENTS | | |
| Very good ingress/egress from both front and rear doors. Seat height makes ingress/egress very easy. | | |

| REAR SEAT | CONSIDERATIONS | RATING |
|-----------------------------------|---|--------|
| Seat Comfort | Overall Seat Comfort, Hip/Shoulder Room | 7 |
| Headroom | Adequacy | 7 |
| Legroom | Adequacy | 7 |
| Seatbelt | Ease of Hook-Up/Release | 7 |
| DRIVERS COMMENTS | | |
| Plenty of room in rear seat area. | | |

| TRUNK | CONSIDERATIONS | RATING |
|--------------------------|---------------------------|--------|
| Lid | Ease of Opening | 7 |
| Lid | Size of Opening | 7 |
| Compartment | Ease of Loading/Unloading | 7.2 |
| DRIVERS COMMENTS | | |
| Plenty of room for gear. | | |

| SLALOM | CONSIDERATIONS | RATING |
|--|---|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.6 |
| DRIVER COMMENTS | | |
| Rear pillar placement interferes with rear visibility. | | |

| PARRALLEL PARK - LEVEL | CONSIDERATIONS | RATING |
|---|---|--------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.7 |
| DRIVER COMMENTS | | |
| Rear window visibility limited due to size. Rear view camera helps if equipped. | | |

| PARRALLEL PARK - INCLINE | CONSIDERATIONS | RATING |
|--|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.7 |
| DRIVER COMMENTS | | |
| Rear pillar placement and small rear window effect rear visibility when backing. | | |

| PARRALLEL PARK – DECLINE | CONSIDERATIONS | RATING |
|---|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.7 |
| DRIVER COMMENTS | | |
| Rear camera helps, if equipped. Rear pillar compromises view. | | |

| REAR 3-POINT TURN | CONSIDERATIONS | RATING |
|--|--|---------------|
| Overall Backing Visibility | Ceiling Height, Dash Height, Pillar Placement, Windshield Size & Distortion | 6.7 |
| DRIVER COMMENTS | | |
| Rear pillars obstruct view. Rear window is small, reducing visibility. | | |

FUEL EFFICIENCY RESULTS

Regular Fuel Vehicles

| VEHICLE | AVERAGE MPG |
|---|-------------|
| Chevrolet Impala 3.6L | 20 mpg* |
| Chevrolet Tahoe 5.3L 2WD | 12 mpg* |
| Chevrolet Tahoe 5.3L 4WD | |
| Chevrolet Caprice 3.6L | 20 mpg* |
| Chevrolet Caprice 6.0L | 16 mpg* |
| Dodge Charger – 3.6L 2.62 | |
| Dodge Charger – 3.6L 3.07 | 20 mpg* |
| Dodge Charger – 5.7L 2.62 | 17 mpg* |
| Dodge Charger – 5.7L AWD | 16 mpg* |
| Ford Police Interceptor Sedan FWD 3.5L | 19 mpg* |
| Ford Police Interceptor Sedan AWD 3.7L | 19 mpg* |
| Ford Police Interceptor Sedan AWD 3.5L EcoBoost | 17 mpg* |
| Ford Police Interceptor Utility AWD 3.7L | 17 mpg* |
| Ford Police Interceptor Utility AWD 3.5L EcoBoost | 15 mpg* |

*Figures are from previous year.